

RECEIVED

WATER WELL REPORT

STATE OF OREGON SEP 28 1976 State Well No. 38s/9E 34ad

(Please type or print) WATER RESOURCES DEPT. SALEM, OREGON State Permit No.

NOTICE TO CONTRACTOR The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

KLAM 12164

(1) OWNER:

Name MELL & WART & BILL BRANDSNESS Address 5930 WASH BURN WAY KLAMATH FALLS, ORE

(2) TYPE OF WORK (check):

New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven [ ] Cable [ ] Jetted [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [ ] Industrial [ ] Municipal [ ] Irrigation [ ] Test Well [ ] Other [X]

(5) CASING INSTALLED:

12 3/4" Diam. from 0 ft. to 42 ft. Gage 250 8 5/8" Diam. from 42 ft. to 1158 ft. Gage 250

(6) PERFORATIONS:

Perforated? [ ] Yes [X] No. Type of perforator used. Size of perforations in, by in.

(7) SCREENS:

Well screen installed? [ ] Yes [X] No. Manufacturer's Name, Type, Diam., Slot size, Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level. Was a pump test made? [X] Yes [ ] No. If yes, by whom? INTERSTATE. Pump test: 430 gal./min. with 8 ft. drawdown after 4 hrs.

(9) CONSTRUCTION:

Well seal—Material used CEMENT. Well sealed from land surface to 42 ft. Diameter of well bore to bottom of seal 15 in. Diameter of well bore below seal 15 1/4 in. Number of sacks of cement used in well seal 30 sacks.

(10) LOCATION OF WELL:

County KLAMATH Driller's well number SE 1/4 NE 1/4 Section 34 T. 38S R. 9E W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 1494 ft. Static level 42 ft. below land surface. Date 8/25/76. Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 7 7/8. Depth drilled 1529 ft. Depth of completed well 1529 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include: SANDY YELLOW SHALE (0-20), GREEN SHALE (20-905), VERY STICKY GREEN SHALE (905-1110), GREEN SHALE (1110-1140), VERY STICKY GREEN SHALE (1140-1150), GREEN SHALE (1150-1174), BROWN SHALE (1174-1190), GRAY SHALE (1190-1254), HARD BLACK SHALE (1254-1269), HARD BLK SHALE & STREAKS GRAY SHALE (1269-1303), BLACK BASALT (1303-1409), BROWN CLAY (1409-1421), VERY HARD BROKEN BROWN CHALK ROCK (1421-1424), HARD BLACK BASALT (1424-1434), HARD BROKEN BLK BASALT (1434-1439), GRAY CLAY (1439-1479), HARD BROKEN BLK BASALT (1479-1498), GRAY CLAY (1498-1494), HARD BROKEN BLK BASALT (1494-1529) WB.

Work started 6/22/76 19 Completed 8/25/76 19 Date well drilling machine moved off of well 8/25/76 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] David M. Storey Date 8/10, 1976 Drilling Machine Operator's License No. 656

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name EE STOREY & SON WELL DRILLING INC (Person, firm or corporation) (Type or print) Address 3847 Hope Klamath Falls ORE [Signed] David M. Storey (Water Well Contractor) Contractor's License No. 601 Date 8/9/10, 1976

(USE ADDITIONAL SHEETS IF NECESSARY)