

(1) OWNER: Rodgers

Name Rogers and Stacy
Address Swan Lake
Olene, Oregon

NOV 28 1962

(11) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? Interstate
Yield: 2400 gal./min. with 35 ft. drawdown after 4 hrs.
" 2800 to 3000 44 " 4 "
" 2000 " 23 " 4 "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water 56 Was a chemical analysis made? Yes No

(2) LOCATION OF WELL:

County Klamath Owner's number, if any—
1/4 1/4 Section 9 T. 38S R. 10E W.M.
Bearing and distance from section or subdivision corner

This well has been filed on before under a Mr. Riley's name of the above address. Therefore it is already located. N72°E - 530 ft. from SW Cor. of NW 1/4 SW 1/4 Section 9.

(3) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 11.

PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(6) CASING INSTALLED:

Threaded Welded
16" Diam. from 0 ft. to 193 ft. Gage 3/16 &
20" Diam. from 0 ft. to 20 ft. Gage 1/4
" Diam. from ft. to ft. Gage

(7) PERFORATIONS:

Perforated? Yes No
Type of perforator used Torch
SIZE of perforations 1/4 in. by 12 in.
45 perforations from 153 ft. to 185 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(8) SCREENS:

Well screen installed Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Slot size Set from ft. to ft.

(9) CONSTRUCTION:

Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.
Was a surface seal provided? Yes No To what depth? 20 ft.
Material used in seal—20 in. casing
Did any strata contain unusable water? Yes No
Type of water? Depth of strata
Method of sealing strata off

(10) WATER LEVELS:

Static level 95 ft. below land surface Date May 10
Artesian pressure lbs. per square inch Date

Log Accepted by:

[Signed] Rodgers Stacy Date 6-3, 1958
By Geo. Polley Fautner
(Owner)

(12) WELL LOG:

Diameter of well inches.
Depth drilled ft. Depth of completed well ft.
Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

MATERIAL	FROM	TO
Reamed hole from 14" to 18" from 0 ft to 215 ft. Then from 115 to 284. Reamed 9 inch hole to 12 1/2 in. Deepened to 325ft 12 1/2"		
Black lava very hard	284	302
Lava (poris with black sand)	302	315
Lava (poris with red cinders)	315	325
12 inch bit 48 inches long left in bottom of hole		

Work started March 4 1958. Completed May 10 1958

(13) PUMP:

Manufacturer's Name Layne and Bowler
Type: Turbine H.P. 100

Well Driller's Statement:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Wilson Drilling Contractor
(Person, firm, or corporation) (Type or print)

Address Box 136 Merrill, Oregon

Driller's well number

[Signed] Walter S. Wilson
(Well Driller)

License No. 169 Date May 22, 1958