Klam
12314

WATER WELL REPORT
STATE OF OREGON

RECEIVED
APR 4 1977
WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 38s/11E-11

State Permit No.

(1) OWNER:
Name LEANORD S. COURNOGER
Address 45540 W 28th S.E.
LANCASTER CALIF 93534

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☒
8" Diam. from 1 ft. to 38 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☐ Yes ☒ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 10 gal./min. with 3 ft. drawdown after 1½ hrs.
Artesian flow g.p.m.
Temperature of water 51 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used CEMENT
Well sealed from land surface to 36 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 4 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County KLAMATH Driller's well number 100
~~NW~~ ¼ ¼ Section 11 T. 38 R. 11 W.M.
Bearing and distance from section or subdivision corner
Lot 17 BLOCK 47 UNIT 2

(11) WATER LEVEL: Completed well.
Depth at which water was first found 315 ft.
Static level 309 ft. below land surface. Date 3-18-77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 8
Depth drilled 326 ft. Depth of completed well 325 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
CLAY & SAND BROWN	0	2	
CLAY & GRAVEL BROWN	2	20	
BOLDERS SMALL BROWN	20	28	
LAVA BROWN	28	30	
	30	315	
Sand COARSE BLACK	315	325	309

Work started 11-13 1975 Completed 3-18 1977
Date well drilling machine moved off of well 3-19 1977

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Denny McClane (Drilling Machine Operator) Date 3-18, 1977
Drilling Machine Operator's License No. 107

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name DENNY McCLANE WELL DRILLING (Person, firm or corporation) (Type or print)
Address 1607 AUSTIN ST, KLAMATH FALLS OREGON 97601
[Signed] Denny McClane (Water Well Contractor)
Contractor's License No. 476 Date 3-23, 1977

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119