NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 9731 within 30 days from the date of well completion.

## WATER WELL REPORT (

STATE OF OREGON (Please type or print)

APR 6:077 State Permit No.

(Do not write above this THER RESOURCES DEPT

(1) OWNER:	(10) LOCATION OF GWELL:		
Name George Crain	County Klamath Driller's well number		
Address Anderson Rd. Merrill, Oregon	SW 14 NE 14 Section 1 T. 395	R. 9E W.M.	
	Bearing and distance from section or subdivision		
(2) TYPE OF WORK (check):	Dearing and about the second		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	32.		
If abandonment, describe material and procedure in Item 12.	(11) WARRED I EVEL Commission II		
	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 230 ft.		
Rotary 街 Driven 🛘 Domestic 🖂 Industrial 🖂 Municipal 🖂	Static level 70 ft. below land s	urface. Date 3/17/77	
Dug   Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Threaded ☐ Welded X 2 50    22	(12) WELL LOG: Diameter of well below casing 20  Depth drilled 1000 ft. Depth of completed well 1000 ft.  Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
PERFORATIONS: Perforated? E Yes   No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL	From To SWL	
Size of perforations $1/8$ in, by $2\frac{1}{2}$ in.	Top Soil Iellow Sandy Clay-Hard Pan	3 8	
24 perforations from 200 ft. to 990 ft.	Gravel	8 9	
perforations fromft. toft.	Yellow Clay & Sand	9 28	
perforations fromft. toft.	Yellow Clay	28 76	
periorations non-	Sandstone	76 92	
(7) SCREENS: Well screen installed?   Yes X No	Hard Yellow Clay	92 108	
Manufacturer's Name	Brown Clay	108 110	
Type Model No	Yellow Clay	110 115	
Diam Slot size Set from ft. to ft.	Yellow Clay	115 126	
Diam. Slot size Set from ft. to ft.	Blue Clay	126 141	
(8) WELL TESTS. Drawdown is amount water level is	Black Clay	141   230	
(8) WELL TESTS:  Drawdown is amount water level is lowered below static level Interstate	Red Gravel or Cinders	230 276	
Was a pump test made? A Yes No H yes, by whom? Pump	Black Sandstone	276   390	
yand: 710 gal./min. with 253 ft. drawdown after 10 hrs.	Black Clay	390 565	
" "	Green Clay	565 895	
" " " "	Hard Shale	895 900	
	Green Clay	900   968	
Bailer test gal./min. with ft. drawdown after hrs.	Hard Clay some white & brown	968 980	
Artesian flow g.p.m.	Black Rock	980 1000	
rature of water 69 Depth artesian flow encounteredft.	Work started 11-1-76 19 Completed 3-18- 1977		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3–14 1977	
Well seal—Material used	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.  Materials used and information reported above are true to my best knowledge and belief.  [Signed]  Drilling Machine Operator')  Drilling Machine Operator's License No.		
and the control of th			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Yes \( \subseteq \text{No Plugs} \) Size: location ft.	Name C & C Enloe Well Drilling		
Did any strata contain unusable water? 🔲 Yes 📅 No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address P.O. Box 323, Dorris, Ca. 96023		
Method of sealing strata off	[Signed] Carl & Eulo		
Was well gravel packed? $\square$ Yes $\square$ No Size of gravel: $3/8 - 3/4$	(Water Well Contr	actor)	
Gravel placed from 0 ft. to 990 ft.	Contractor's License No. 503 Date	/2 , 1977	