

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

RECEIVED
SEP 15 1966
WATER WELL REPORT
STATE ENGINEER
SALEM, OREGON

NCKLAN 12495
RECEIVED
NOV 10 1966
CRAIN well #3
STATE ENGINEER
G-3833 M. OREGON
State Permit No. _____

(1) OWNER:

Name George F. Crain
Address 6551 Moyina Way
Klamath Falls, Oregon

(2) LOCATION OF WELL:

County Klamath Driller's well number _____
SW $\frac{1}{4}$ NE $\frac{1}{4}$ Section 1 T. 39S R. 9 E W.M.
Bearing and distance from section or subdivision corner _____

(3) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
Abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(6) CASING INSTALLED:

Threaded Welded
12" Diam. from 0 ft. to 7.00 ft. Gage 250
10" Diam. from 6.00 ft. to 12.00 ft. Gage 250
" Diam. from _____ ft. to _____ ft. Gage _____

(7) PERFORATIONS:

Perforated? Yes No
Type of perforator used _____
Size of perforations in. by in.
perforations from _____ ft. to _____ ft.
perforations from _____ ft. to _____ ft.
perforations from _____ ft. to _____ ft.
perforations from _____ ft. to _____ ft.
perforations from _____ ft. to _____ ft.

(8) SCREENS:

Well screen installed? Yes No
Manufacturer's Name _____
Type _____ Model No. _____
Slot size _____ Set from _____ ft. to _____ ft.
Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.

(9) CONSTRUCTION:

Well seal—Material used in seal Cement
Depth of seal 13.0 ft. Was a packer used? yes
Diameter of well bore to bottom of seal 10 in.
Were any loose strata cemented off? Yes No Depth _____
Was a drive shoe used? Yes No
Was well gravel packed? Yes No Size of gravel: _____
Gravel placed from _____ ft. to _____ ft.
Did any strata contain unusuable water? Yes No
Type of water? _____ depth of strata _____
Method of sealing strata off _____

(10) WATER LEVELS:

Static level _____ ft. below land surface Date _____
Artesian pressure _____ lbs. per square inch Date _____

(11) WELL TESTS: Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
Yield: 450 gal./min. with unk ft. drawdown after _____ hrs.
" " " " " "
" " " " " "
" " " " " "
Bailer test _____ gal./min. with _____ ft. drawdown after _____ hrs.
Artesian flow _____ g.p.m. Date _____
Temperature of water _____ Was a chemical analysis made? Yes No

(12) WELL LOG: Diameter of well below casing 10

Depth drilled 1569 ft. Depth of completed well 1562 ft.
Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

MATERIAL	FROM	TO
top soil	6	9
yellow chalk	9	20
sand	20	145
Blue chalk	145	200
chalk and Bldms	200	305
rock	305	310
chalk	310	445
casing chalk	445	465
chalk	465	500
black sand	500	520
casing chalk	520	600
chalk sand streaks	600	1190
shoulders		
rock	1190	1562
water strata		
	1360	
	1480	

Work started May 6 1965 Completed Feb 10 1966
Date well drilling machine moved off of well Feb 10 1966

(13) PUMP:

Manufacturer's Name Western
Type twister H.P. 60

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME W.L. Hartley & Son
(Person, firm or corporation) (Type or print)
Address Beranza Oregon
Drilling Machine Operator's License No. 120
[Signed] Robert F. Hartley
(Water Well Contractor)
Contractor's License No. 164 Date May 1 1966

RECEIVED 39/9-1G
 SMITH AND WESTVOLD **RECEIVED**
 ENGINEERING & SURVEYING NOV 10 1966 Klamath
 Tuxedo 4-3691 or 2-3908
 STATE ENGINEER
 LEM. OREGON

2333 Summers Lane

~~REGISTERED~~ - KLAMATH FALLS, OREGON

RECEIVED
 SEP 16 1966
 STATE ENGINEER
 LEM. OREGON

May 6, 1965

GEORGE CRAIN LEGAL DESCRIPTION FOR WELL SITE

A parcel of land situated in the SW $\frac{1}{4}$ NE $\frac{1}{4}$ of Section 1, T 39 S, R 9 E W, Klamath County, Oregon, more particularly described as follows:

Beginning at a point on the north - south centerline of said Section 1, said point being S 00°47'38" E a distance of 90.00 feet from the iron pin marking the northwest corner of the SW $\frac{1}{4}$ NE $\frac{1}{4}$ of said Section 1; thence continuing S 00°47'38" E a distance of 50.00 feet; thence N 89°12'22" E at right angles to the north - south centerline of said Section 1 a distance of 110.00 feet; thence N 00°47'38" W parallel with the north - south centerline of said Section 1 a distance of 50.00 feet; thence S 89°12'22" W a distance of 110.00 feet to the point of beginning.

The above described parcel of land contains 0.13 acres, more or less.


 Lyle C. Smith