NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT STATE OF OREGON

KLAM 12563 WATER WELL REPORT

	12563	j	
1	State Well No.	395/9E.81	5c

SALEM, OREGON 97310 within 30 days from the date of well completion.

APR 1 3 1981

(Please type or print)

Diate	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
			£		
State	Permit	No.		•••••	
			State Permit No.	State Permit No	

of well completion. WATER RESOURCES DEPTwrite at	bove this line)	NO	***************************************	***************************************
OPEGON				
()	(10) LOCATION OF WELL:	_		
Name REAMES GOLF & COUNTRY CLUB Address 873 Box 105	County KAAMATA Driller's well		<u></u>	
KLAMATH FALLS ORC	SW 14 NW 14 Section 8 T. 32			W.M
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivi	lsion corne	<u> </u>	
New Well M Deepening Reconditioning Abandon				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL Completed			·
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed		~	_
Rotary Driven	Depth at which water was first found		4.0	1/0/0
Cable Jetted	Static level # ft. below land			18/0
Dug	Artesian pressure lbs. per squ	are inch.	Date	
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well	l below co	sing /	OTES
" Diam. from ft. to ft. Gage	Depth drilled 265 ft. Depth of com			7026
10 14 " Diam. from + 1 tt. to 3 9 tt. Gage 4 5	Formation: Describe color, texture, grain size		-440	materials
"Diam. from ft. to ft. Gage	and show thickness and nature of each strat	tum and a	quifer pe	e netrate c
PERFORATIONS: Perforated?	with at least one entry for each change of form position of Static Water Level and indicate pr			
Type of perforator used	MATERIAL	From	То	SWL
Size of perforations in. by in.	Redainders ThoubDERS	<i>A</i>	11	-
perforations from	GRAY BASALT ROCK	W	16	
perforations from	BLOWN SAM STONE	16	34	
perforations from	GRAY SANDSTINE	34	5-5	
	Blown SANdSTONE	53	68	
(7) SCREENS: Well screen installed? Yes No	GRAY LAVA	68	113	ļ
Manufacturer's Name	BROWN SANDETONE	1/3	124	ļ
Type	Bluz gray LAVA	124	157	
Diam. Slot size Set from ft. to ft.	RED CINDER RECT	110	165	-
	BLUCREAY LAVA	1/5	1/0	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Red LVA	218	238	
Was a pump test made? ☐ Yes Mr No If yes, by whom?	BLACK LAVA	8.50	242	
Yield: gal./min. with ft. drawdown after hrs.	BLUE LAVA	242	350	
ILIFT 550 GIPM @ 180'" /2"	Blue 9RAYLAVA	200	265	ļ
" 6636PM@ 250" 4/2"				<u> </u>
Bailer test gal./min. with ft. drawdown after hrs.		_		<u> </u>
Artesian flow g.p.m.	\$ //5	-	<u> </u>	
perature of water 75 Depth artesian flow encountered ft.	Work started 2 19 19 Comple	eted 4/	14/0	19
	7/4/	red T	1101	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7/0	101	
Well seal—Material used	Drilling Machine Operator's Certification		t sumon	
Well sealed from land surface to	This well was constructed under m Materials used and information reported			
Diameter of well bore to bottom of seal	best knowledde and beligf.	2) s	1 /9/	9
Diameter of well bore below seal in. Number of sacks of cement used in well seal 5 sacks	[Signed] (Drilling Machine Operator)	Date	fl./	., 19.4.
Number of sacks of cement used in well seal sacks How was cement grout placed?	Drilling Machine Operator's License No.	7	10	••••
	Water Well Contractor's Certification:		_	
	This well was drilled under my juristrue to the best of my knowledge and be	diction ar elief.	nd this r	eport is
Was a drive shoe used? Yes No Plugs Size: location ft.	Name EESTOREY SON He		Line	140
Did any strata contain unusable water? Yes No	(Person, firm or corporation)			••••
Type of water? depth of strata	Address 3727 FOR	~ ~ ~ C	111	
Method of sealing strata off	[Signed]	, 		
Was well gravel packed? Yes No Size of gravel:	(Water Well Con			
Gravel placed from ft. to ft.	Contractor's License No Date	4/7/	7/	, 19