WATER WELL REPORT

STATE OF OREGON

RECEIVED

MAR 1 1 1983

WATER RESOURCES DEPTate Permit No. SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name Cell Tech Inc.	County Klamath Driller's well number
Address 4519 Cannon St.	SE 4 SE 4 Section 25 T. 39S R. 9E . W.M.
City Klamath Falls State Or.	Tax Lot # Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location: HWy • 39
New Well ☑ Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 15
Petamo Air VI Primar D	Static level 11 ft. below land surface. Date 3-8-83
Rotary Mud Dug Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
Cable Bored Thermal: Withdrawal Reinjection	(12) WELL LOG: Diameter of well below casing6"
CASING INSTALLED: Steel M Plastic	Depth drilled 102 ft. Depth of completed well 101 ft.
Threaded Welded	Formation: Describe color, texture, grain size and structure of materials; and show
6" Diam from1 ft. to99 ft. Gauge250	thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level
"Diam fromft. toft. Gauge	and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
	Brown Top Soil o 1
(6) PERFORATIONS: Perforated? Yes X No	Hard Brown Clay 1 8
Type of perforator used	Sandy Brown Clay 8 15
Size of perforations in. by in.	Brown Clay 15 19
perforations from ft. to ft.	black Sand 19 74
perforations from	Blue Clay 74 81
perforations from ft. to ft.	Blue Sand 81 95 Gravel and Sand 95 101 11'
(7) SCREENS: Well screen installed? ☐ Yes ₩ No	Gravel and Sand 95 101 11' Sandy Blue Clay 101 102
Manufacturer's Name	Dainty Dine Oray 101 102
Type	
Diam. Slot Size Set from ft.	
Diam. Slot Size Set from ft. to ft. (2) WELL TESTS. Drawdown is amount water level is lowered	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made?	
d: gal./min. with ft. drawdown after hrs.	
n n	
Air test 30 gal./min. with drill stem at 80 ft. 1 hrs.	
Bailer test gal/min. with ft, drawdown after hrs.	
Artesian flow g.p.m.	
perature of water 53 Depth artesian flow encounteredft.	Work started 3-7 1983 Completed 3-8 1983
(9) CONSTRUCTION: Special standards: Yes □ NoX	Date well drilling machine moved off of well 3-8 1983
Well seal—Material usedCement	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision. Motorials used
Diameter of well bore to bottom of seal	and information reported above the true to my best knowledge and belief.
76	[Signed] Willing Machine Operator) Date 3-9, 19.83
Number of sacks of cement used in well seal sacks How was cement grout placed? Pumped	Drilling Machine Operator's License No.
A STATE OF THE PARTY OF THE PAR	Water Well Contractor's Certification:
Chapterine Company of the Company of	This well was drilled under my jurisdiction and this report is two to
Was pump installed? NO	the nest of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Roger Chancellor Well-drilling (Person, firm or corporation)
Did any strata contain unusable water? X Yes No	Address 5233 Walley will In. K. Falls, Or
Type of Water? Surfice depth of strata 15' Method of scaling strata off Congine a good Company	
Method of sealing strata off Casing and Cement Was well gravel packed? □ Yes ♥ No Size of gravel:	[Signed] My (Water Well Contractor)
Was well gravel packed? ☐ Yes ※ No Size of gravel:	Contractor's License No. Date 3-9 ,1983