NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

KLAM 12768 WATER WELL REPORT

JUSTATE OF OREGON
(Please type or print)

WATER RESOURCES DEPTINE)

KLAM 12768

5		101/05 20/1
ell	No.	375/9E-300A

State	Permit	No.	***************************************

SALEM DEFO	M			
(1) OWNER:	(10) LOCATION OF WELL:			
Name O.C. WeBB-Bower	County BLAMATh Driller's well number			
Address VOBo & 1600	SE 1/4 NW 1/4 Section 30 T. 395 R. 9 E W.M.			
	Bearing and distance from section or subdivision	corner		
(2) TYPE OF WORK (check):				
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well	1.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 3/	<i>D</i>	ft.	
Rotary Driven Domestic Industrial Municipal	Static level 25 ft. below land sur	face. Date 6	130/70	
Cable	Artesian pressure lbs. per square i	inch. Date		
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well belo		9	
"Diam. from ft. to ft. Gage 550" Diam. from 1/2 ft. to 4/ ft. Gage 550	Depth drilled 340 ft. Depth of complete	d well 340	<u> 11.</u>	
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and			
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in			
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate princip	al water-bearin	ng strata.	
pe of perforator used	MATERIAL	From To	SWL	
Size of perforations in. by in.	GRAVEL FILL	0 3		
perforations from ft. to ft.	PACKED SAND	3 60		
perforations from ft. to ft.	YELLGIN CLAY	6 85		
perforations fromft. toft.	GREEN STALLE 3	35- 310		
(E) CODENIC	GREENSLALE ESTREAMS 3	10		
(7) SCREENS: Well screen installed? Yes No	DF SANd	340	WB	
Manufacturer's Name				
Type Model No			····	
Diam, Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is				
lowered below static level				
Was a pump test made? Yes No If yes, by whom?				
Vield: gal./min. with ft. drawdown after hrs.				
RLIFT 90 "GPM@ 200" "				
70 "6PM @ 135" / "				
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.				
nperature of water & Depth artesian flow encountered ft.	Work started 6/29/78 19 Completed	6/30/70	19	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	,//30/70	19	
Well seal—Material used CEMENT	Drilling Machine Operator's Certification:			
Well sealed from land surface toftftftft	This well was constructed under my d Materials used and information reported at			
Diameter of well bore to bottom of seal 9 18 in.	best knowledge and belief			
Diameter of well bore below sealin.	[Signed] Ballowy Da	ate <i>7/10/79</i>	? 19	
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)			
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.			
Brand name of bentonite	Water Weil Contractor's Certification:			
Number of pounds of bentonite per 100 gallons		ion and this .	enort ia	
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? Yes 🗆 No Plugs Size: location ft.	Name BESTOREY YSONNELLDR	ILLING 1	NC	
Did any strata contain unusable water? Yes	(Person, firm or corporation)	(Type or pri	nt)	
Type of water? depth of strata	Address 3847 Hof	<u> </u>		
Method of sealing strata off	[Signed] & & Story			
Was well gravel packed? Yes No Size of gravel:	(Wast Well Contract	(or)	کھ	
Gravel placed from ft. to ft.	Contractor's License No Date	110/10	, 19	