STATE OF OREGON

WATER WELL REPORT (as required by ORS 537.765)



(for official use only)

(1) OWNER: SEP 0 3 1985	(10) I OCATION OF WELL by local doc	onintion.
Name Gene Parker WATER RESOURCES DEPT	(10) LOCATION OF WELL by legal description: County Klamath SN 4 NN 4 of Section 21 of	
Address 1521 McClellan CALEM, OREGON	Township 35 south Range 7 eas	1.
City Klamath Falls, State OR.97601	(Township is North or South) (Range	s East or West)
	Tax Lot ± 900 Lot 0009 Riock & Subdivision W LLLL Edill SOIL R LV Cr	
(2) TYPE OF WORK (check):	Hatates MAILING ADDRESS OF WELL (or nearest address) The Rapids on	
New Well ☑ Deepening □ Reconditioning □ Abandon □	Hwy 97 N.	
If abandonment, describe material and procedure in Item 12.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLETED WELL:	
Rotary Air 🛛 Driven 🗌 Domestic 🖾 Industrial 🗌 Municipal 🗍 Thermal:	Depth at which water was first found 125	
Rotary Mud Dug Irrigation Withdrawal Reinjection	Static level +2 ft. 5000 land su	
Cable Bored Piezometric Grounding Test		
(5) CASING INSTALLED: Steel Plastic	(12) WELL LOG: Diameter of well below casing 6 inch Depth drilled 278 ft. Depth of completed well 278 ft.	
Threaded Welded X	Formation: Describe color, texture, grain size and structure of mate	rials: and show thickness
6 "Diam. from +1 = ft. to 91 ft. Gauge .250	and nature of each stratum and aquifer penetrated, with at least on	e entry for each change of
ft. Gauge	formation. Report each change in position of Static Water Lev water-bearing strata.	ei and indicate principal
LINER INSTALLED: Steel Plastic	MATERIAL From	
none Threaded Welded W	Sandy top soil	0 2 swL
ft. To Gauge ft. Gauge	Sandy brown clay	2 8
(6) PERFORATIONS: Perforated? \(\sigma\) Yes \(\frac{1}{2}\) No	Packed brown sand	8 16
Size of perforations in. by in.		6 29
perforations from ft. to ft.		9 39
ft. to ft.		9 41
perforations from ft. to ft.		1 44
(7) SCREENS: Well screen installed? ☐ Yes ♣ No		4 53
Manufacturer's Name		3 89
TypeModel No.		9 125
Diam. Slot Size Set from ft. to ft.	Coarse black sand 12	
Diam Slot Size Set from ft. to ft.	Blue clay 12	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Blue 6lay w/streaks of black 17	
below static level	sand	185 +2
Was a pump test made? Yes	Blue clay with streaks of sand 18	
d: gal./min. with ft. drawdown after hrs.	and and gravel	272 +2
mir 75 GPM with stem set at 250' 1 hr.	Gray clay 27	
Air test 25 gal./min. with drill stem at 35 ft. 1 hrs.		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
uperature of water 54 Depth artesian flow encountered ft.	Date work started 8,23,85 /completed 8,	07 07
(9) CONSTRUCTION: Special standards: Yes \(\subseteq \) No \(\subseteq \)	, completed 2	27,85 8,27, ₁₉ 85
Well seal—Material usedcement_and_bentonite		
Well sealed from land surface toft.	(unbonded) Water Well Constructor Certification (if applicable):	
Diameter of well bore to bottom of seal	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.	
Diameter of well bore below seal	1	
Amount of sealing material 8 cement 3/4 bent sacks pounds pounds	[Signed] Date	, 19
How was cement grout placed? <u>pumped from bottom of seal</u> up to the ground surface.	(bonded) Water Well Constructor Certification:	
up to the ground Surface.	Bond 20821134 Issued by: Western Su	rety Co.
YV	(number) (Surety Company Name)	
Was pump installed? Type	On behalf of Norm Sevey (type or print name of Water Well Constructor)	
Was a drive shoe used? 🔼 Yes 🗌 No Plugs Size: location		
Type of Water? NONE depth of strata	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief:	
Method of sealing strata off none	(Simul Maria Va. a.	
Was well gravel packed? Yes No Size of gravel:	(Signed) Harm Sevel (Water Well Constructor)	
Gravel placed fromft. toft.	(Dated) 8,28,85	
NOTICE TO WATER WELL CONCERNIONAR	D. WARTE Process of a	