NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

Was well gravel packed? [Yes No Gravel placed from

New Well

Name

Rotary

WATER WELL REPORT

STATE OF OREGON

395/136-926 State Permit No.

(Please type or print) (Do not write above this line)

01 H01 0011 1011 1011 1011 1011 1011 10		·····
1) OWNER:	(10) LOCATION OF WELL:	
Vame HAROLD WILLIAMS	County KLHMHTH Driller's well n	umber /
Address RT / 130× 934	NW 14 SE 14 Section 9 T. 395	R. 13E W.M.
BONANZA OR 97623	Bearing and distance from section or subdivisi	ion corner
(2) TYPE OF WORK (check):		
New Well Deepening Reconditioning Abandon		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.	
Rotary Driven Domestic Industrial Municipal	Static level ft. below land	surface. Date
☐ Jetted ☐ ☐ Irrigation X Test Well ☐ Other ☐		
(5) CASING INSTALLED: Welded Welded	(40) TYPIT TOG	11
(5) CASING INSTALLED: "Threaded □ Welded □	(12) WELL LOG: Diameter of well below casing	
" Diam. fromft. Gage	Doput danie / D D D D D D D D D D D D D D D D D D	
" Diam. from ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,	
	with at least one entry for each change of forma	ation. Rep <mark>ort each change in</mark>
(6) PERFORATIONS: 1/A Perforated? Yes No.	position of Static Water Level and indicate pri	ncipal water-bearing strata.
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	LAYA ROCK	448 570
perforations from ft. to ft	BROKENLAVA	570 590
perforations from ft. to ft.		590 598
perforations from ft. to ft		
In .		
(7) SCREENS: W// Well screen installed? Yes No		
Manufacturer's Name		
Type Model No.		1
Diam. Slot size Set from ft. to ft.		+
Diam. Slot size Set from ft. to ft.		+ + + - +
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	INDEA TO SEE AND TO SEE	
a pump test made? Yes No If yes, by whom?	V	
rield: gal./min. with ft. drawdown after hrs	WATER RESCURCES DEPT	
" " " "	TO CALEM ORRGON 8	
,		
Railer test gal./min. with ft. drawdown after hrs	b.	
Temperature of water 4 Bepth artesian flow encountered	Work started $f = 3 - 19$ 79Comple	ted 8-18- 1971
	Date well drilling machine moved off of well	8-12-1979
(9) CONSTRUCTION: HAP		
Well seal—Material used	Drilling Machine Operator's Certification This well was constructed under my	
Well sealed from land surface to	Materials used and information reported above are true to my	
Diameter of well bore to bottom of sealin.	best knowledge and belief.	· 0-111
Diameter of well bore below sealin.	[Signed] Man Date 3-14-, 1979	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	1095
How was cement grout placed?		
And the state of t	Water Well Contractor's Certification:	35-45 3 (3 t
The state of the s	This well was drilled under my jurison true to the best of my knowledge and be	
Was a drive shoe used? Yes No Plugs Size: location ft		
Did any strata contain unusable water? Tryes I No	(Person, firm or corporation)	
Type of water? depth of strata	Address 12.0. 13.0% 237,-	BONANZA
Method of sealing strata off	[Signed] Inan Hartley	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Wall Con	tractor)
St to St	Contractor's License No 726 Date	8-14- 1976