Corrected by WRD staff

NOTICE TO WATER WELL CONTEACTOR
The original and first copy of the port
are to be filed with the

WATER RESOURCES DEPARTMENT (Please type or print)

Gravel placed from _____ft. to _____ft.

State Well No. 395/136-966

WATER RESOURCES DEPARTMENT OF OREGON
SALEM, OREGON 97310
Within 30 days from the date
of well completion TER RESOURCES

(Please type or print)
(Do not write above this line)

State	Well No.	95/ 136 -94
State	Permit No.	***************************************

SALEM. OREGON	
1) OWNER:	(10) LOCATION OF WELL:
Tame HAROLD WILLIAMS	County KLAMATH Driller's well number
ddress BONANZA OR 97623	NW 4 S F 1/4 Section 9 T. 398 R. 13 E W.M.
	Bearing and distance from section or subdivision corner
2) TYPE OF WORK (check):	NW14 SEY4 Section & Township 395.
New Well ፟ Deepening □ Reconditioning □ Abandon □	Ronge 13 E
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 230 ft.
Rotary Driven Domestic Industrial Municipal	Static level / 95 ft. below land surface. Date //-28-78
Cable	Artesian pressure ///4 lbs. per square inch. Date
WAVE (TEST)	2 11
CASING INSTALLED. Threaded Welded	(12) WELL LOG: Diameter of well below casing
" Diam. fromft. toft. Gage	Depth drilled 405 ft. Depth of completed well 405 ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
Diam. Irom	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	ROCK & SANDSTONEBRN / 20
perforations from ft. to ft.	CHALK 20 32
perforations fromft. toft.	CHALK 32 50
perforations from ft. to ft.	CHARCTONE + BOLDERS 86 94
	SANDSTONE +BOLDERS 86 94 IAVA ROCK 94 220 195
•	IAVA BROKEN & WATER 220 230 230
Manufacturer's Name	LAVA BROKEN + WATER 230 311
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	LAVA BURNT 338 359
	BROWN SANDSTONE 359 368
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	LAVA, BROKEN 368 395
Was a pump test made? Y Yes \(\subseteq \text{No If yes, by whom? VALEY PUMF} \)	CINDERS & BURNT LAVA 395 400
Yard: /200 gal./min. with /0 ft. drawdown after / hrs.	LAVA ROCK 405
" "	
" " "	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water 62 Depth artesian flow encountered ft.	Work started //- 3 - 19 > Completed //- 28 - 19 7
	Date well drilling machine moved off of well 11-28-197
(9) CONSTRUCTION:	Drilling Machine Operator's Certification:
Well seal—Material used NONE	This well was constructed under my direct supervision
Well sealed from land surface to	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well hore to bottom of seal	
Number of sacks of cement used in well seal	[Signed] Date 12-4, 1978
How was cement grout placed?	Drilling Machine Operator's License No. 1015
And the state of t	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report i
413	true to the best of my knowledge and belief.
Was a drive shoe used? Yes A No Plugs Size: location ft.	Traine was a second
Did any strata contain unusable water? Yes No	(Person, firm as composition) A AMDIH TOULS
Type of water? GOD depth of strata	Address Address Address
Method of sealing strata off w/A	[Signed] (Kanny Hart KE)
Was well gravel packed? ☐ Yes 🌠 No Size of gravel:	(Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No