WATER WELL REPORT
STATE OF OREGON

Klam
13771 C

RECEIVED
AUG 25 1981
WATER RESOURCES DEPT
SALEM, OREGON

State Well No. 40/8E-20
State Permit No.

(1) OWNER:
Name Dale Taylor
Address 1950 Fargo, St.
City Klamath Falls, State Or 97601

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary Air ☒ Driven ☐
Rotary Mud ☐ Dug ☐
Cable ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐
Thermal: Withdrawal ☐ Reinjection ☐

(5) CASING INSTALLED:
Steel ☐ Plastic ☐
Threaded ☐ Welded ☐
6" Diam. from 2 ft. to 47 ft. Gauge 250
" Diam. from ft. to ft. Gauge

LINER INSTALLED:
" Diam. from ft. to ft. Gauge

(6) PERFORATIONS:
Perforated? ☐ Yes ☒ No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
Air test 10 GPM gal./min. with drill stem at 425 ft. hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

CONSTRUCTION:
Special standards: Yes ☐ No ☐
Well seal—Material used cement
Well sealed from land surface to 35 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 12 sacks
How was cement grout placed? pumped in trimie

Was pump installed? Type HP Depth ft.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Klamath Driller's well number
¼ ¼ Section 20 T. 40 R. 8 E W.M.
Tax Lot # Lot Blk Subdivision
Address at well location: lot 18 block 3 Cedar Trails tract 1083

(11) WATER LEVEL: Completed well.
Depth at which water was first found 405 ft.
Static level 387 ft. below land surface. Date 8-20-81
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 6
Depth drilled 447 ft. Depth of completed well 447 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
top soil loose rock	0	18	
red clay & bolders	18	38	
bolders enbeded in clay	38	121	
hard blue basalt (cement)	121	237	
brown lava	237	252	
extra hard blue lava	252	275	
red lava & cinders	275	302	cemted
hard blue basal rocks	302	405	water
broken lava	405	420	
brown cinders	420	447	
& water			

Work started 8-10-81 19 Completed 8-20-81 19
Date well drilling machine moved off of well 8-20-81 19

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Charles E. Hartley (Drilling Machine Operator) Date 8-20-81
Drilling Machine Operator's License No. 233

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Charles E. Hartley (Person, firm or corporation) (Type or print)
Address 4779 S. 6th Klamath Falls, Or. 97601
[Signed] Charles E. Hartley (Water Well Contractor)
Contractor's License No. 145 Date 8-20-81, 19

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

SP*12658-690