NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

KLAM 13795

WATER WELL REPORT

KLAM 13795

STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 40S/8E-21CC

State Permit No.

(1) OWNER:

Name John R Martin

Address 4939 Samac CT Klamath Falls, Ore.

(2) TYPE OF WORK (check):

New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☑ Driven ☐
Cable ☑ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☑

8 5/8" Diam. from +1 ft. to 28 ft. Gage .250
4" Pipe Liner Diam. from +1 ft. to 405' ft. Gage Sch 160
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☑ Yes ☐ No.

Type of perforator used saw

Size of perforations 1/4 in. by 4" in.

300 perforations from 345 ft. to 405 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☑ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☑ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "

Bailer test 10 gal./min. with 0 ft. drawdown after 2 hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement

Well sealed from land surface to 28 ft.

Diameter of well bore to bottom of seal 12 in.

Diameter of well bore below seal 6 in.

Number of sacks of cement used in well seal 14 sacks

How was cement grout placed? Placed Thru 1 1/4" Induction Tube

Was a drive shoe used? ☐ Yes ☑ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☑ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☑ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Klamath Driller's well number

SW ¼ SW ¼ Section 21 T. 40 R. 8 W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 378 ft.

Static level 292 ft. below land surface. Date 6/15/79

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 407 ft. Depth of completed well 407 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top soil	0	3	
Brown clay & Boulders	3	16	
Firm brown lava	16	32	
Soft brown lava - caving	32	80	
Hard brown lava	80	125	
Brown lava with seams of clay	125	147	
Hard brownish black lava	147	168	
Soft brown lava - caving	168	206	
Hard brownish black lava	206	333	
Hard black lava	333	356	
Reddish brown cinderous	356	405	292
lava conglomerate			
Hard lava	405	407	

RECEIVED
JUN 20 1979
WATER RESOURCES DEPT
SALEM, OREGON

Work started 5/25 1979 Completed 6/15 1979

Date well drilling machine moved off of well 6/15 1979

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Gilbert M Powell (Drilling Machine Operator) Date 6/18, 1979

Drilling Machine Operator's License No. 114

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Powell Well Drilling (Person, firm or corporation) (Type or print)

Address P.O. Box 114 Keno, Ore.

[Signed] Gilbert M Powell (Water Well Contractor)

Contractor's License No. 454 Date 6/18, 1979

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119