NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER "RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT KURM

STATE OF OREGON

(Please type or print)

State Well No	405	8E-3	46
---------------	-----	------	----

(Do not write above this line)

State	Well No. 405 8E-3464	
State	Permit No.	

(1) OWNER:	(10) LOCATION OF WELL:			
Name Donald Mathis	County Klamath Driller's well number			
Address Ashland Star Route Klamath Falls, Oregon 97601	SE 1/4 NW 1/4 Section 34 T. 40S R. 8E W.M.			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
-				
New Well Deepening Reconditioning Abandon If abandonment, describe material and procedure in Item 12.				
	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 65 ft.			
Domestic M. Industrial □ Municipal □	Static level 20 ft. below land surface. Date 7/10/70			
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date			
(5) CASING INSTALLED: Threaded Welded 65/8 Diam. from 0 ft. to 21 ft. Gage •250	(12) WELL LOG: Diameter of well below casing 61			
" Diam. fromft. toft. Gage	Depth drilled 95 ft. Depth of completed well 95 ft.			
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,			
(6) PERFORATIONS: Perforated? Var. X No.	with at least one entry for each change of formation. Report each change in			
Turbutudi. 1 Ica (5-110.	position of Static Water Level and indicate principal water-bearing strata.			
Type of perforator used	MATERIAL From To SWL			
Size of perforations in. by in.	Brown Lava Rock 0 60			
perforations from ft. to ft.	Black Lava Rock 60 75			
perforations fromft. toft.	Black Lava - trace Sand 75 95			
perforations fromft. toft.				
(7) SCREENS: Well screen installed? ☐ Yes ☐ No				
Manufacturer's Name	the state of the s			
Type Model No				
Diam. Slot size Set from ft. to ft.	DEALIVED			
Diam. Slot size Set from ft. to ft.	REGEIVED			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	AUG 3 1 1979			
s a pump test made? Yes No If yes, by whom?	WATER RESOURCES DEPT			
radd: gal./min. with ft. drawdown after hrs.	SALEM. OREGON			
11 11 11				
# # n	V. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.			
Bailer test 30 gal./min. with 10 ft. drawdown after 2 hrs.				
esian flow g.p.m.				
Temperature of water Depth artesian flow encountered ft.	Work started 7/9 19 79 Completed 7/10 19 79			
(9) CONSTRUCTION:	Date well drilling machine moved off of well 7/11 19 79			
Well seal—Material used Cement	Drilling Machine Operator's Certification:			
Well sealed from land surface to 21	This well was constructed under my direct supervision			
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.			
Diameter of well bore below seal6 in.	[Signed] [Aul 4] Enlow Date 7/11 19 79			
Number of sacks of cement used in well seal6	(Drilling Machine Operator)			
How was cement grout placed?Pump	Drilling Machine Operator's License No. 342			
*	Water Well Contractor's Certification:			
· ·	This well was drilled under my jurisdiction and this report is			
Was a drive shoe used? Tyes \(\) No Plugs Size: location ft.	true to the best of my knowledge and belief.			
Did any strata contain unusable water? Tyes & No	Name C & C Enloe Well Drilling (Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address P.Q. Box 323 Dorris CA 96023			
Method of sealing strata off	(41 6 A			
[Signed] LAV U-Culos				
, voil it is made to				
TI, IO II,	Contractor's License No503 Date 7/11 , 1979			