WATER WELL REPORT STATE OF OREGON

RECEIVED 395/8E-7 da

NOV 191981
State Permit No.
WATER RESOURCES DEPT

SALEM, OREGON

1) OWNER:	(10) LOCATION OF WELL:		
Jame John Bianchi	County Klamath Driller's well number		
address 3220 Round Lake Rd.	NE 4 SE 4 Section 7 T. 39S R. 8E	W.M.	
Sity Klamath Falls State Oregon	Tax Lot # Lot Blk Subdivision		
2) TYPE OF WORK (check):	Address at well location:		
New Well X Deepening □ Reconditioning □ Abandon □	(11) WATER LEVEL: Completed well.		
f abandonment, describe material and procedure in Item 12.	Depth at which water was first found 750	ft.	
3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 330 ft. below land surface. Date 1		
Robery Air XI Driven	Artesian pressure lbs. per square inch. Date		
and Bored Thermal: Withdrawal Reinjection	(12) WELL LOG: Diameter of well below casing		
5) CASING INSTALLED: Steel M Plastic Threaded Welded N Welded N Threaded Threaded Threaded N Welded N Threaded	Depth drilled 210 ft. Depth of completed well 210 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
LINER INSTALLED:	MATERIAL From To	SWL	
	Brown Top Soil 0 3		
	Hard Brown Clay 3 7		
6) PERFORATIONS: Perforated? Yes No	Sandy Brown Clay 7 23		
Type of perforator used	Brown Lava 23 30		
Size of perforations in. by in.	Brown Clay & Lava 30 42		
perforations from	Hard Black Rock 42 68	 -	
perforations from	Brown Lava 68 80		
perforations from ft. to ft.	Broken Lava & Brown Clay-		
7) SCREENS: Well screen installed? Yes X No	Stone 80 85		
Manufacturer's Name	Hard Brown Claystone 85 88		
Type Model No	Hard Blue Shale 88 99		
Diam. Slot Size Set from ft. to ft.	Hard Black Rock 99 150		
Slot Size Set from St. to ft. to Set from S	Broken Lava Rock (W.B.) 150 210	<u>130'</u>	
a pump test made? Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
Air test 150 gal./min, with drill stem at 170 ft. I hrs.			
Beiler test gal/min. with ft. drawdown after hrs.	7		
sian flow g.p.m.			
Temperature of water 53 Depth artesian flow encountered ft.	Work started] 0 - 28 19 8] Completed]] - 4	181	
(9) CONSTRUCTION: Special standards: Yes 🗆 No 👪	Date well drilling machine moved off of well 131-4 181		
Well seal—Material usedComon t	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my direct supervision. Materi	iala ugod	
Diameter of well bore to bottom of seal12in.	and information reported above are true to my best knowledge and belief.		
Diameter of well bore below sealin.	[Signed] May W. Mantolle Date 11-171981		
Number of sacks of cement used in well seal20sacks	Drilling Machine Operator's License No		
How was cement grout placed?PumpedFromtheBottom	Drining Massinie Operator & Dicense 1401.0044		
up.	Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to		
Was pump installed?	the best of my knowledge and belief.		
Was a drive shoe used? 🗆 Yes 🕱 No Plugs, Size: location ft.	NameRoger Chancellor Well-Drilling (Type or print)		
Did any strata contain unusable water? Year No	Address 5233 Valley View In, K. Falls. 97601		
Type of Water? depth of strata	[Signed] Mayou Whancelle		
Method of sealing strata off	(Water Well Contractor)	*****	
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	Contractor's License No. 6.9.3 Date 11-17	, 1981.	

Gravel placed from