NC **KLAM 14322** 

NOTICE TO WATER WELL CONTRA

The original and first cody

of this report are to be
filed with the

STATE ENGINEER SALES

CCT 14 1965 WATER WELL REPORT

KLAM

STATE ENGINEER, SALEM, OF THE ENGINEER OF OREGON within 30 days from the data ALEM OREGON (Please type or print)

State Well No.

within 30 days from the data ALEN	OREGON (Please ty)	pe or print) State Permit No	***************************************	
(1) OWNER:		(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
Name A.R.Klepper		Was a pump test made? Yes No If yes, by whor		
Address Rt. 3 Box 292, Klamath, Falls, Ore.		Yield: gal./min. with ft. drawdo		hrs.
		., , , , , , , , , , , , , , , , , , ,		"
(2) LOCATION OF WELL:				
County Klamath Driller's well number			lown after	2 hrs.
1/4 1/4 Section 29 T. 395 R. 8e W.M.		Artesian flow g.p.m. Date		
Bearing and distance from section or subdivision corner		Temperature of water Was a chemical analysis	4	es A No
		(12) WELL LOG: Diameter of well below	casingO	
		Depth drilled 80 ft. Depth of completed		
		Formation: Describe by color, character, size of mater show thickness of aquifiers and the kind and nature of stratum penetrated, with at least one entry for each	ial and struc f the materic change of f	ture, and al in each ormation.
·		MATERIAL	FROM	то
(3) TYPE OF WORK (check):		Topsoil	0	3
Well Deepening Reconditioning Abandon		1108011	10	
pandonment, describe material and procedure in Item 12.		Soft greenish shale	3	15
(4) PROPOSED USE (check):	(5) TYPE OF WELL:			
Domestic 🛣 Industrial 🗆 Municipal 🗆	Rotary 🔲 Driven 🗀	Brown sandstone	15	39
	Cable A Jetted			
• -	Dug	Sand and gravel	39	43
	aded Welded 🕅	first water	+	~
6" " Diam. from oft. to	10. ft. Gage	Brown sandstone	43	74
" Diam. from ft. to ft. Gage		Sand and gravel	74	80
ft. to		water	14	
(7) PERFORATIONS: Perfo	orated? 📆 Yes 🗌 No			
Type of perforator used Act. torch	· \	Gravel pad placed from	78	80
Size of perforations 250" in. by 4" in.  160 perforations from 40° ft. to 80° ft.				
160 perforations from 40	ft. to 801 ft.			
perforations from ft. to ft.				
perforations from ft. to ft.			<u> </u>	
, perforations from ft. to ft. perforations from ft. to ft.				
			-	
(8) SCREENS: Well screen insta	alled? 🗆 Yes 🛣 No			
Manufacturer's Name				
2				
ım. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.			8/8/65	19
		Date well drilling machine moved off of well	8/8/65	19
(9) CONSTRUCTION:		(13) PUMP:		
Well seal-Material used in seal Concrete		Manufacturer's Name		
Depth of seal 24. the was a packer used? Yes.		Type: H.P.		
Diameter of well bore to bottom of seal		Water Well Contractor's Certification:		
Were any loose strata cemented off? Yes [	ANo Depth			
Was a drive shoe used? ☐ Yes 🛣 No Was well gravel packed? ☐ Yes 🛣 No S	ize of gravel:	This well was drilled under my jurisdiction true to the best of my knowledge and belief.	and this	report is
Gravel placed from ft. to ft. to	_			
Did any strata contain unusuable water?  Yes No		NAME Roy Powell Well Drilling (Type of print)		
Type of water? depth of strata		Address P.O. Box 123 Keno Oregon		
Method of sealing strata off				
(10) WATER LEVELS:		Drilling Machine Operator's License No114		
Static level 721 ft. below land	d surface Date 8/8/65	[Signed](Water Well Contractor		
Artesian pressure lbs. per squ	Contractor's License No210 Date8/8		19	