

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

KLAM 14324

WATER WELL REPORT

KLAM 14324

STATE OF OREGON (Please type or print) (Do not write above this line)

RECEIVED JUN 5 1968

39/8-29

STATE ENGINEER SALEM OREGON

(1) OWNER:

Name DON JOHNSTON Address RT 3 Box 399 Klamath Falls, Ore

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [x] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [] Test Well [x] Other []

CASING INSTALLED:

Threaded [] Welded [x] Diam. from 0 ft. to 20 ft. Gage 2.50

PERFORATIONS:

Perforated? [] Yes [x] No

Type of perforator used

Table with columns: Size of perforations in. by in., perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No

Manufacturer's Name, Type, Model No., Diam. Slot size, Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 49 ft. below land surface Date 5/18/68 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [x] Yes [] No If yes, by whom? Valley Pump Co. Rate: 400 gal./min. with 62 ft. drawdown after 4 hrs. Baller test 100 gal./min. with 0 ft. drawdown after 2 hrs. Artesian flow g.p.m. Date Temperature of water 59 degrees Was a chemical analysis made? [] Yes [x] No

(10) CONSTRUCTION:

Well seal—Material used BENTONITE Depth of seal 20 ft. Diameter of well bore to bottom of seal 12 in. Were any loose strata cemented off? [] Yes [x] No Depth Was a drive shoe used? [] Yes [x] No Did any strata contain unusable water? [] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Klamath Driller's well number 1/4 1/4 Section 29 T. 39S R. 8E W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 10"

Depth drilled 220 ft. Depth of completed well 219 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Includes entries like Top soil, brown sandstone, white diatomite, green shale, sandy green shale-water, light green sticky shale, soft black sandstone, pea gravel-water bearing, yellowish brown clay, green shale, black sandstone-gravel, soft black sand - water bearing - casing.

Hole showed cave from 116' - 220' Hole to be used as stock well Work started 4/15 1968 Completed 5/20 1968 Date well drilling machine moved off of well 5/20 1968

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] W. Herbert Powell Date 5/20, 1968 (Drilling Machine Operator)

Drilling Machine Operator's License No. 114

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Powell Well Drilling (Person, firm or corporation) (Type or print)

Address P.O. Box 114 Keno, Ore.

[Signed] W. Herbert Powell (Water Well Contractor)

Contractor's License No. 454 Date 5/20, 1968