

RECEIVED

KLAM 14516

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

AUG 11 1966

WATER WELL REPORT

STATE ENGINEER, SALEM 10, OREGON (Please type or print) STATE OF OREGON SALEM OREGON

State Well No. 40/9-5 J State Permit No.

(1) OWNER: Name Richard H. Smith Address Rt. # 1 Box # 894A Tingley Road Klamath Falls Oreg.

(2) LOCATION OF WELL: County Klam. Driller's well number N.E. 1/4 S.E. 1/4 Section 5 T. 40 S R. 9 E. W.M. Bearing and distance from section or subdivision corner

(3) TYPE OF WORK (check): New Well [x] Deepening [] Reconditioning [] Abandon [] Abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check): Domestic [x] Industrial [] Municipal [] Irrigation [] Test Well [] Other [] (5) TYPE OF WELL: Rotary [] Driven [] Cable [x] Jetted [] Dug [] Bored []

(6) CASING INSTALLED: Threaded [] Welded [x] 6" Diam. from 0 ft. to 140 ft. Gage 1/4 In.

(7) PERFORATIONS: Perforated? [] Yes [x] No Type of perforator used Size of perforations in. by in.

(8) SCREENS: Well screen installed [] Yes [x] No Manufacturer's Name Type Model No. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION: Well seal—Material used in seal Cement & Puddled clay Depth of seal 140 ft. Was a packer used? yes Diameter of well bore to bottom of seal 10 in. Were any loose strata cemented off? [] Yes [x] No Depth Was a drive shoe used? [x] Yes [] No Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft. Did any strata contain unusable water? [x] Yes [] No Type of water? Surface Depth of strata 9 Feet Method of sealing strata off Casing

(10) WATER LEVELS: Static level 17 ft. below land surface Date 7-21-66 Artesian pressure lbs. per square inch Date

(11) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [x] No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs.

(12) WELL LOG: Diameter of well below casing 6 In. Depth drilled 1045 ft. Depth of completed well 1045 ft. Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

Table with columns: MATERIAL, FROM, TO. Rows include: Brown sandy soil (0-3), Brown clayey sandstone (3-16), Yellow claystone (16-28), Green claystone (28-180), Fine sandstreaks in green claystone producing approx. 2 G.p.M. (180-195), Grey claystone (195-230), Green claystone (230-515), Grey clay stone (515-535), Green claystone with water bearing streaks producing approx. 8 g.p.m. (535-605), Grey claystone (605-640), Green claystone (640-935), Sandy green claystone water bearing (935-1025), Medium hard grey basalt rock with crevices & water bearing (1025-1045).

Work started 6-25-1966 Completed 7-21-1966 Date well drilling machine moved off of well 7-22-1966

(13) PUMP: Manufacturer's Name Type: H.P.

Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME James A. Roberts (Person, firm or corporation) (Type or print) Address 148 East Main St. Klamath Falls Oreg. Drilling Machine Operator's License No. 184 [Signed] James A. Roberts (Water Well Contractor) Contractor's License No. 147 Date 8-9-1966