

The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE OF OREGON

(Do not write above this line)

State Well No. 405/9E3482
State Permit No.

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

RECEIVED
DEC 20 1976

Klamath
14580
SAL

(1) OWNER: WATER RESOURCES DEPT.

Name LISKEY FARMS INC. OREGON
Address Box 467
MERRILL ORE

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
6 7/8" Diam. from 0 ft. to 19 1/2 ft. Gage 250
19 1/2" Diam. from 19 1/2 ft. to 250 ft. Gage 250

(6) PERFORATIONS:

Perforated? Yes No
Type of perforator used
Size of perforations in. by in.
perforations from 0 ft. to 19 1/2 ft.
perforations from 19 1/2 ft. to 250 ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
AIR LIFT 150 GPM @ 261 FT 1
Baller test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 189 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used BENTONITE
sealed from land surface to 19 ft.
Diameter of well bore to bottom of seal 9 7/8 in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal 5 sacks
Number of sacks of bentonite used in well seal 5 sacks
Brand name of bentonite AQUA-CELL
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plug Size: location ft.
Did any strata contain unusable water? Yes No
Type of water depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel: ft.
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County KLAMATH Driller's well number
SE 1/4 NE 1/4 Section 34 T. 40S R. 9E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 80 ft.
Static level 17 ft. below land surface. Date 12/13/76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6
Depth drilled 261 ft. Depth of completed well 261 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
BROWN CLAY TOPSOIL	0	2	
YELLOW CLAY	2	13	
GRAY CLAY	13	45	
HARD GRAY SHALE	45	261	W/B

Work started 12/13/76 19 Completed 12/13/76 19
Date well drilling machine moved off of well 12/13/76 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] [Signature] Date 12/16, 1976
(Drilling Machine Operator)
Drilling Machine Operator's License No. 656

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name E E STOREY & SON WELL DRILLING, INC.
(Person, firm or corporation) (Type or print)
Address 3847 Hope K FALLS, ORE
[Signed] [Signature] (Water Well Contractor)
Contractor's License No. 601 Date 12/16, 1976