NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

(Please type or print)

(Do not write above this line)

	•
State Permit No.	***************************************
State Lemmi 140.	***************************************

	(10) LOCATION OF WELL:		
(1) OWNER:	17 1 1		
(1) OWNER:  Name Mr Ronald C. Slaton  Address Taylor Road	county Klamath Driller's well nu	mber 10E	1
Address Taylor Road	SW 1/4 SW 1/4 Section 25 T. 40s	R. LOE	<u> W.M.</u>
Address Taylor Road Merrill, Oregon  Merrill Oregon	Bearing and distance from section or subdivision	n corner	Approx.
(9) TVPE OF WORK (check):	うう そっさ Past and 800 feet North	of the	<u> </u>
New Well Deepening Reconditioning Abandon	GONS W corner of S 25. T 40 S	R 10E	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):		165	ft
	7/10		.5/15/78 ***
Cable	Static level 142 ft. below land st	urface. Da	te' -'
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure ————————————————————————————————————	e inch. Da	te
CASING INSTALLED: Threaded Welded 4 Gage 250	(12) WELL LOG: Diameter of well b		6 200 ft.
" Diam. from ft. to ft. Gage " Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a and show thickness and nature of each strature.		
PERFORATIONS: Perforated? ☐ Yes 🖔 No.	with at least one entry for each change of format position of Static Water Level and indicate prin	tion. Report	each change in
Type of perforator used	MATERIAL	From	To SWL
	Yellow chalk or clay	0	26
	Bla ck lava rock	26	28
perforations fromft. toft.	Brown lava rock	28	34
perforations from	Black lava	34 2	¥7
perforations from ft. to ft.	Brown and black lava	47	115
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	Black lava rock	115	165
Manufacturer's Name	Brown and red broken lava	165	175 142
Type Model No.	Black lava rock broken	175	200 142
Diam. Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	:		
Was a pump test made?  Yes XNo If yes, by whom?			
Wald: gal./min. with ft. drawdown after hrs.			
Air Lifted from 200 feet 20 G.P.M.			
	.45		
II and made made made take and	. , ;		
Bailer test gal./min. withft. drawdown after firs.			
Artesian flow g.p.m.			
perature of water 65 Depth artesian flow encountered		ed May 1	5 <sub>19</sub> 78 <sub>19</sub> 78
(9) CONSTRUCTION:	Date well drilling machine moved off of well	riay 1)	19 7
Well seal—Material used Cement	Drilling Machine Operator's Certification:		
20	This well was constructed under my	direct s	upervision.
Well sealed from land surface toft.  Diameter of well bore to bottom of seal,in.	Materials used and information reported best knowledge and belief.		
Diameter of well bore below sealin.	[Signed] Juny Wood (Drilling Machine Operator)	Date May	· 15 <sub>19</sub> 78
Number of sacks of cement used in well seal	(Drilling Machine Operator)	1012	,
How was cement grout placed?	Drilling Machine Operator's License No.		•
and get lain less that			
and the first of t	Water Well Contractor's Certification:		ta .
The state and state the state and st	This well was drilled under my jurisdi true to the best of my knowledge and bel		this report is
Was a drive shoe used?   Yes No. Plugs Size: location	Name Wilson Drilling Cont, Inc		
Did any strata contain unusable water? 🛘 Yes 🔁 No	(Person, firm or corporation) Address P.O. Box 136, Merrill,		or print)
Type of water? depth of strata	Address P.O. Box 136, Merrill,	uregon	7/033
Method of sealing strata off	21 le 1 2	1 . 1	I .
Was well gravel packed? ☐ Yes 10 No Size of gravel:	[Signed] (Water Welf Contr	actor)	&y@
Gravel placed fromft toft.	Contractor's License No. 169 Date	May 15	19 78
ATLANCE DIRECTIONS	,		1J19