KLAM 14776

Klam 14776

The original and first day.

JAN 26 1966

STATE OF OREGON ADDRESS. AN 26 1966 STATE OF OREGON Please type or print) STATE ENGINEER, SALEM 10, OREGON within 30 days from the date. of well completion. G3418 State Permit No. Drawdown is amount water level is lowered below static level (1) OWNER: (11) WELL TESTS: NamMarvin Retterath Was a pump test made? 🖺 Yes 📋 No If yes, by whom? Address Yield: 500 Merrill, Oregon gal./min. with ft. drawdown after hrs. ,, (2) LOCATION OF WELL: Bailer test gal./min. with ft. drawdown after hrs. Klamath County Driller's well number Artesian flow g.p.m. Date S W S W _{14 Section} 32 5_{R.} 11 E W.M. T. Temperature of water 62 Was a chemical analysis made?
Yes
No Bearing and distance from section or subdivision corner
1885 feet North of the Said Soth Sec. Line (12) WELL LOG: Diameter of well below casing 8 inch Depth drilled 210 ft. Depth of completed well 210 525 feet east of the said west sec. line Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation. MATERIAL FROM (3) TYPE OF WORK (check): Top Soil 0 Well 🕇 Deepening [Reconditioning [2 Abandon | Brown clay andonment, describe material and procedure in Item 12. 35 Brown clay W/ shells of sand 60 106 Tan Chalk (4) PROPOSED USE (check): (5) TYPE OF WELL: Brown and black broken lava Driven 🗀 Domestic [] Industrial [] Municipal [] 106 (water Jetted 140 OTh Irrigation Z Test Well D Other $\overline{\Box}$ Bored Dug 137 15 4NVCD 140 XXXXXXXXXX Clay W/ gravel (6) CASING INSTALLED: Threaded | Welded | 154 155 Brown rock 165 Brown clay w/ gravel 155 " Diam. from ft. to ft. Gage Broken Lava 165 167" Diam. from ft. to ft. Gage 167 187 Brown Chalk 187 191 Red lava (7) PERFORATIONS: Perforated? 🗌 Yes 💆 No Rock w/ crevice (all cuttings washed away) Type of perforator used 205 191 Size of perforations in. by 205 210 perforations from ft. to Red lava rock perforations from ft. to perforations from ft. to ft. perforations from ft. to perforations from ft. to (8) SCREENS: Well screen installed Yes No Manufacturer's Name Model No. ... 19 61 July 19 61 July Work started Completed ₁₉ 61 Diam. Slot size Set from ft. to ft. July Date well drilling machine moved off of well (9) CONSTRUCTION: (13) PUMP: Well seal-Material used in seal cemented Manufacturer's Name Depth of seal 20 ft. Was a packer used? yes Diameter of well bore to bottom of seal _____in. Water Well Contractor's Certification: Were any loose strata cemented off? Tyes Yes Was a drive shoe used?
Yes No This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was well gravel packed?

Yes No Size of gravel: ... Gravel placed from _____ ft. to ____ ft. NAME WILSON DRILLING CONTRACTOR (Type or print) Did any strata contain unusable water?

Yes X No (Person, firm or corporation) Address Box 136, Merrill, Oregon Type of water? Depth of strata Method of sealing strata off Cemented Drilling Machine Operator's License No. 122 & 201 (10) WATER LEVELS: ft. below land surface Date 7/6/61 Static level 84 Contractor's License No.69 Date June Artesian pressure lbs. per square inch Date