NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT.

SALEM, OREGON 97310 NOV 25 1980 (Please type or print) within 30 days from the date of well completion ATED DESCRIBERS (Please type or print)

declar sibb
State Well No. 405/13E-3166
/
State Permit No

of well completionWATER RESOURCES (19 mor write above this line)

(1) OWNER:	(10) LOCATION OF WELL:			
• •	CountyKlamath Driller's well number			
Name Carl Rajnus Address Rt.2 Box 784 Klamath Falls, Ore. 97601	N. W. & N. W. % Section 31 т. 40S	R. 12E	} •	W.M.
Address 2002 DON /OT ATAMAMI PALLS, OLG. 97001	Bearing and distance from section or subdivision	n corner		
(2) TYPE OF WORK (check):				
New Well Deepening Reconditioning Abandon				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):		.97		ft.
The state of the s	Depth at which water was miss round)to 7.7	/15/80
Jetted Domestic Lindustrial Lindustrial Lindustrial	Static level 197 ft. below land s			<u>,/ 15/ 0</u> 0
Bored Irrigation Test Well Other	Artesian pressure lbs. per squar	e inch. 1	Date	
(5) CASING INSTALLED: Threaded □ Welded 2. 2.50	(12) WELL LOG: Diameter of well below casing 12			
Type of perforator used	MATERIAL	From	То	SWL
Size of perforations in. by in.	top soil	0	2	
perforations from ft. to ft.	boulders & hardpan	2	4	
perforations from	brown sandstone	4	29	
perforations from ft. to ft.	brown & gray lava & clay	29	35	
	yellow clay & boulders	35	41	
(7) SCREENS: Well screen installed? Yes XX No	gray sandstone	41	_55	
Manufacturer's Name	black & white granite	55	76	
Type Model No.	yellow clay	76	130	7.00
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	brown shale	130 233	233 391	197
Diam. Slot size Set Holli Lt. to	black sandstone	391	446	11
(8) WELL TESTS: Drawdown is amount water level is lowered below static level Intersaate	gray sandstone brown sandstone	446	480	- 11
a pump test made? Yes \(\subseteq \text{No If yes, by whom? Pump CO.} \)	black cinders	480	502	**
200 43	gray sandstone	502	575	11
Yield: gal./min. with ft. drawdown after hrs.				
*				
er test gal./min. with ft. drawdown after hrs.		ļ		
esian flow g.p.m.		<u> </u>	,	<u> </u>
Temperature of water 63 Depth artesian flow encountered ft.				19 8
(9) CONSTRUCTION:	Date well drilling machine moved off of well	11/15)	19 80
Well seal—Material used Cement Well sealed from land surface to 19 ft. Diameter of well bore to bottom of seal 16 in. Diameter of well bore below seal 12 in. Number of sacks of cement used in well seal 14 sacks How was cement grout placed?	Drilling Machine Operator's Certification This well was constructed under my Materials used and information reported best knowledge and belief [Signed] Cohn A. Van Meterials (Drilling Machine Operator) Drilling Machine Operator's License No.	direct above Date	are true	vision. e to my
	Water Wall Contractor's Contidentian			
Was a drive shoe used? ☐ Yes ₹ No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes ★ No	Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name John A. Van Meter (Person, firm or corporation) (Type or print)			
Type of water? depth of strata	AddressP.O. Box 204 Malin, Ore	976	32	
Method of sealing strata off	[Signed] Little all Mis	To	•	
Was well gravel packed? ☐ Yes ▼ No Size of gravel:	[Signed] Cwater Well Con	ractor)		
Gravel placed fromft. toft.	Contractor's License No Date	TT/23	5 	, ₁₉