## NOTICE TO WATER WELL CONTROL TO BE CONTROL T

KI KAN State Well No.

41/10-10 bb

STATE ENGINEER, SALEM, ORE STATE ENGINEER type or print) within 30 days from the date of well completion.

SALEM. OREGON write above this is SALEM. OREGON write above this line)

State Permit No. .....

(1) OWNER:	(10) LOCATION OF WELL:			
Name Ralph Stearns	County Klamath Driller's well number			
Address Merrill, Oregon	N W 4N W 4 Section 10 T. 41 S R. 10 E W.M.			
	Bearing and distance from section or subdivision			
(2) TYPE OF WORK (check):	1600 Ft. South N W Corner			
New Well 🚺 Deepening 🗌 Reconditioning 🗎 Abandon 🖂		W. C		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	اام		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 10k ft.			
Rotary Driven Domestic Industrial Municipal	Static level 81 ft. below land s	urface D	ate Tow	
Cable	Artesian pressure lbs. per squar			
CASING INSTALLED:  Threaded   Welded 1/2 20 ft Gage 250    12 "Diam. from Top ft to 172 ft Gage 188    "Diam. from ft to ft Gage    "PERFORATIONS:  Perforated? Yes   No.	(12) WELL LOG:  Diameter of well below casing  Depth drilled 172  ft. Depth of completed well 172  ft.  Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
Type of perforator used Factory Perforated	MATERIAL	From	то	SWL
1/90				
Size of perforations 1/0: in. by 5 in.  1712 perforations from 65 st to 172 st	Top Soil Gravely clay		3 7	
perforations from	Blue clay		66	
perforations from	Gravely clay		75	
perforations from ft. to ft.	Cemented Gravel		105	
(7) SCREENS: Well screen installed? ☐ Yes ▼ No	Loose Gravel		170	
Manufacturer's Name	Cemented Gravel		172	
Type Model No				
Diam Slot size Set from ft. to ft.				
Diam Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is				
lowered below static level				
Was a pump test made? TYes   No If yes, by whom valley Pump				
Yield: 1100 gal./min. with 12 ft. drawdown after 4 hrs.				
" " " "				
" "				
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.				
mperature of water 58 Depth artesian flow encountered ft.	Work started Dec. 18 19 71 Complete	d Jan.	, 10	1972
(5) CONSTRUCTION:	Date well drilling machine moved off of well	Fev. 5		19 42
Well seal—Material used Cement  Well sealed from land surface to 19 ft.  Diameter of well bore to bottom of seal 20 in.  Diameter of well bore below seal 11 in.  Number of sacks of cement used in well seal 15 sacks  Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's Certification:  This well was constructed under my Materials used and information reported best knowledge and belief.  [Signed] Orilling Machine Operator's License No.	above ar	re true	to my, 19.72.
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	This well was drilled under my jurisdi		this re	eport is
Was a drive shoe used?  Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.			
Did any strata contain unusable water?   Yes  No	Name OREN STOREY WELL DRILLING (Person, firm or corporation)	"I (Type	e or print	t)
Type of water? depth of strata	Address Box 347 Dorris, Calif.	96023		
Method of sealing strata off		,		
Was well gravel packed? Yes No Size of gravel:	[Signed]	ictor)		
Gravel placed from ft. to ft.	Contractor's License No. ,191 Date	Feb. 7		., 19
	,			