Corrected by WRD staff	KLAM		* 4	
	149972 40S	11E 3	34 CC	
NOTICE TO WATER WELL CONTRACTOR APR 24 1967 The original and first copy of this report are to be filed with the STATE ENGINEER	LL REPORT	In-	3 12	
filed with the <b>GINEER</b> STATE ENGINEER, SALEM, OREGON 97310 M OREGO (Please type or print) of well completion. State Well No. <b>IIIIII</b> State Well No. <b>State Well No.</b>				
(1) OWNER:	(11) WELL TESTS: Drawdown is amount lowered below static	water leve evel Diin	el is	
Name Charles Duncan	Was a pump test made? 🛛 Yes 🗌 No If yes, by who		nter	
Address St. Rt. Malin, Oregon	Yield: 750 gal./min. with 93 ft. drawdo	wn after	2 hrs.	
			"	
(2) LOCATION OF WELL:		lown after	hrs.	
County Klamath Driller's well number N.W 1/4 N.W. 1/4 Section 3 T. 41 & R. 11 & W.M.	Artesian flow g.p.m. Date			
	Temperature of water 64 Was a chemical analysis made? 🗌 Yes 👿 No			
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below casing12			
	Depth drilled 734 ft. Depth of completed well 734 ft.			
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.			
	MATERIAL	FROM	то	
(3) TYPE OF WORK (check):	top soil	0	<u>2</u> 51	
Well Deepening Reconditioning Abandon	boulders and clay	2	3	
In pandonment, describe material and procedure in Item 12.	gray sandstone	<u> </u>	<u>647</u> 670	
(4) PROPOSED USE (check): (5) TYPE OF WELL:	sticky gray clay layers of sticky clay and	047	010 4	
Domestic Industrial Municipal Cable Difference	sandstone	670	679	
Irrigation T Test Well Other Dug Bored	gray lava and sticky clay	679	708	
(6) CASING INSTALLED: Threaded U Welded	gray and brown lava	708	721 000	
14 " Diam. from 0 ft. to 19 ft. Gage 71"	brown sandstone	721	134	
ft. Gage				
	· · · · · · · · · · · · · · · · · · ·	1	· · · · ·	
(7) PERFORATIONS: Perforated? 🗆 Yes 🛣 No	· · · · · · · · · · · · · · · · · · ·		······································	
Type of perforator used				
Size of perforations in. by in.				
perforations from	· · · · · · · · · · · · · · · · · · ·		<u></u>	
perforations from			<u> </u>	
perforations from ft. to ft.			· · · ·	
perforations from ft. to ft.				
(8) SCREENS: Well screen installed?  Yes X No			· · · · · · · · · · · · · · · · · · ·	
Manufacturer's Name			· · · · · · · · · · · · · · · · · · ·	
Model No		_ <b>_</b>		
Dram Slot size Set from ft. to ft.	Work started 2/15 19 67 Completed 4	/17	<sub>19</sub> 67	
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well 4/1	9	<sub>19</sub> 67	
(9) CONSTRUCTION:	(13) <b>PUMP</b> :			
Well seal-Material used in seal Portland cement	Manufacturer's Name			
Depth of seal	Type:			
Diameter of well bore to bottom of seal	Water Well Contractor's Certification:	Water Well Contractor's Certification:		
Were any loose strata cemented off? Ves X No Depth	This well was drilled under my jurisdiction and this report is			
Was a drive shoe used? □ Yes ₩ No Was well gravel packed? □ Yes □ No Size of gravel:	true to the best of my knowledge and belief.			
Gravel placed from	NAME John A. Van Meter			
Did any strata contain unusable water? 🗍 Yes 🍸 No	(Person, firm or corporation) (Type or print) P O Box 201 Malin Oregon			
Type of water? depth of strata	Address F.O. BOX 204 Mailin, Oregon			
Method of sealing strata off	Drilling Machine-Operator's License No			
(10) WATER LEVELS:	Isimult Sala Park to			
Static level 1271 ft. below land surface Date 4/17/67	[Signed] [And Contractor]			
Artesian pressure lbs, per square inch Date	Contractor's License No. 170 Date			
(USE ADDITIONAL SE	HEETS IF NECESSARY)	<u> </u>		

-