## WATER WELL REPORT STATE OF OREGON

KLAM2

## RECEIVED

MAY 23 1983

State Well No. 355 108-24 cb

WATER RESOURCES DEPT. State Permit No. SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:		
Name New Port Property Acquisition, Inc.	County Klamath Driller's well number		
Address P.O. Box 26	NW 4 SW 4 Section 24 T.35 S		
City Sprague River State OR 97639	Tax Lot # Lot Blk	Subdivision	
(2) TYPE OF WORK (check):	Address at well location:		
New Well ☑ Deepening □ Reconditioning □ Abandon □  If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
	Depth at which water was first found	7ft.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):		and surface. Date 9-27-82	
Rotary Air W Driven Domestic Industrial Municipal		er square inch. Date 9-27-8	
Rotary Mud	(12) WELL LOG: Diameter of well below		
(E) CLACIDIC INCOMALLED			
(5) CASING INSTALLED: Steel M Plastic  Threaded  Welded M	Depth drilled 679 ft. Depth of completed well 679 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level		
12 "Diam from +1 ft to 232 ft Gauge 250			
	and indicate principal water-bearing strata.	osition of Static Water Level	
LINER INSTALLED:	MATERIAL	From To SWL	
	Sandy Top Soil	From To SWL. 0 7	
(A) DEDECO ATTONIC	Brown Sandstone	7 10 +2	
(6) PERFORATIONS: Perforated? ☐ Yes No Type of perforator used	Brown Clay	10 14	
Size of perforations in. by in.	Brown Sandstone	14 16 +2	
	Brown Claystone	16 19	
perforations from	Blue Claystone	19 50	
perforations fromft. toft.	Grey Claystone	50 113	
perforations from	Brown Shale & Streaks of -		
(7) SCREENS: Well screen installed?   Yes  No	Claystone	113 152	
Manufacturer's Name	Soft Brown Rock	152 170	
Type	Soft Brown Clay	170 175	
Diam. Slot Size Set from ft. to ft.	Hard Blue Claystone	175 183	
Diam. Slot Size Set from ft. to ft.	Soft Brown Clay	183 192	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Soft Brown Rock & Streaks Of		
Has a pump test made? ▼ Yes □ No If yes, by whom? Valley Pump	Soft Brown Clay	192 210	
eld: gal./min. with ft. drawdown after hrs.	Brown Claystone	210 222	
II	Rlue Claystone - hard	222 240	
Air test gal/min, with drill stem at ft. hrs.	Brown Claystone	240 304	
Bailer test gal./min. with ft. drawdown after hrs.	Blue Shale	304 310	
rtesian flow 2 g.p.m.	Rrown Claystone Continued on another sheet	310 325	
mperature of water $67$ Depth artesian flow encountered $476$ ft.			
9) CONSTRUCTION: Special standards: Yes No No No	Work started 9-0 19 82 Complete Date well drilling machine moved off of well	d 9-28 1982 9-28 1982	
Well seal—Material used Cement	Drilling Machine Operator's Certification:	<u> </u>	
Well sealed from land surface toft.		morrisian Matarialarea	
Diameter of well bore to bottom of seal16 in.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.		
Diameter of well bore below seal12 in.	[Signed] Date 10-12, 1982.		
Number of sacks of cement used in well seal	(Drilling Machine Operator) Drilling Machine Operator's License No. 1171		
low was cement grout placed?Pumped		h.h.(.+	
evernous and established a second declaration and an analysis of the second sec	Water Well Contractor's Certification:		
TO NO NO	This well was drilled under my jurisdiction and this report is true to		
Was pump installed? NO	the best of my knowledge and belief.  Name NORM Sevey Well Drilling, Inc.		
Was a drive shoe used?   Yes X No Plugs Size: location ft.  Did any strata contain unusable water?   Yes X No	(Tenson, tirm or corporation) (Tune or print)		
ype of Water? depth of strata	Address 800 Old Midland Rd. Klaj	nath Falls. OR	
Method of sealing strata off	[Signed] Parm Sever	*******************************	
Vas well gravel packed? ☐ Yes KI No Size of gravel:	(water well Contracto	r) _	
ravel placed from ft to ft	Contractor's License No. 408 Date	10-12 , 1982	

## WATER WELL REPORT

STATE OF OREGON

RECEIVED State Well No. 35s/10E-24cb

WATER RESOURCES DEPT EPErmit No. \_\_\_\_\_ SALEM, OREGON

(1) OWNER: Continued From Another Sheet	(10) LOCATION OF WELL:		
Name New Port Property Acquisition, Inc.	County Klamath Driller's well number		
Address P.O. Box 26	NW 4 SW 4 Section 24 T.35 S		
City Sprague River State OR 97639	Tax Lot # Lot Blk	Subdivision	
(2) TYPE OF WORK (check):	Address at well location:		
New Well □ Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
	Depth at which water was first found	ft.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level ft. below land surface. Date		
Rotary Air Driven Domestic Industrial Municipal Rotary Mud Dug Irrigation Test Well Other	40 A A A A A A A A A A A A A A A A A A A	er square inch. Date	
Rolary Mud   Dug   Irrigation   Test Well   Other   Thermal: Withdrawal   Reinjection	(12) WELL LOG: Diameter of well below casing		
(5) CASING INSTALLED: Steel   Plastic	(70	completed well 679 ft.	
(5) CASING INSTALLED: Steel  Plastic  Threaded  Welded	Formation: Describe color, texture, grain size and structure of materials; and show		
"Diam. from	thickness and nature of each stratum and aquifer pend for each change of formation. Report each change in	etrated, with at least one entry	
"Diam. fromft. toft. Gauge	and indicate principal water-bearing strata.	position of Static water Level	
LINER INSTALLED:	MATERIAL	From To SWL	
	Grey Claystone	325 336	
(A) DEDTOD ATTORY	Brown Clay	336 343	
(6) PERFORATIONS: Perforated? ☐ Yes ☐ No Type of perforator used	Blue Shale	343 347	
	Grey Sandrock	347 364	
	Blue Shale	364 370	
perforations from ft. to ft.	Grey Sandstone	370 382	
perforations from	Blue Claystone	382 437	
perforations from ft. to ft.	Black Rock	437 442	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Blue Claystone	442 444	
Manufacturer's Name	Black Rock	444 476	
Type Model No.	Fractured Black Rock	476 485 +2	
Diam. Slot Size Set from ft. to ft.	Black Sandrock	485 492 +2	
Diam. Slot Size Set from ft. to ft.	Grey Claystone	492 498	
(8) WELL TESTS: Drawdown is amount water level is lowered	Black Rock & Streaks of -	7776 7770	
below static level	Blue Claystone	498 520	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	Brown Claystone	520 536	
Ad: gal./min. with ft. drawdown after hrs.	Grey Sandstone	536 542	
// # # # # # # # # # # # # # # # # # #	Black Fractured Rock	542 555 +2	
Air test gal./min. with drill stem at ft. hrs.	Grey Claystone - hard	555 593	
Bailer test gal./min. with ft. drawdown after hrs.	Black Rock	593 610	
rtesian flow g.p.m.	Brown Claystone	610 679	
mperature of water Depth artesian flow encountered ft.	Work started 9-8 1982 Complete	0.00	
(9) CONSTRUCTION: Special standards: Yes \( \text{No} \) No \( \text{No} \)	Date well drilling machine moved off of well 9-28 1982		
Well seal—Material used	Drilling Machine Operator's Certification:	7.00 00	
Well sealed from land surface to ft.	This well was constructed under my direct s	unorgicion Motoriola used	
Diameter of well bore to bottom of seal in.	and information reported above are true to my b	est knowledge and belief.	
Diameter of well bore below sealin.	[Signed] (Drilling Machine Operator)	Date 10-12, 1982	
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator) Drilling Machine Operator's License No. 1171		
How was cement grout placed?	Drilling Machine Operator's License No	A. A. A. A	
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is true to		
Was pump installed? Type HP Depth ft.	the best of my knowledge and belief.		
Was a drive shoe used?	Name Norm Sevey Well Drilling. Inc.  (Person, firm or corporation) (Type or print)		
Did any strata contain unusable water?	Address 800 Old Midland Rd, Klamath Falls, OR		
Type of Water? depth of strata			
Method of sealing strata off	(Water Well Contractor)		
Was well gravel packed?	Contractor's License No. 408 Date	10-12 , 19.82	
Gravel placed from ft. to ft.	,		