NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97316 within 30 days from the date of well completion.



LAM WATER WELL REPORT

STATE OF OREGON (Please type or print)

Stata	Wall	Νo	35/12	-22	K

State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount lowered below static le	water lev	el is
Name Ernest L. Clements	Was a pump test made? Yes No If yes, by whom		
Address Route 1, Box 2	Yield: gal./min. with ft. drawdov		hrs.
Bonanza, Oregon	" " "		n
(2) LOCATION OF WELL:	" " "		"
County Driller's well number	Bailer test gal./min. with ft. drawdo	wn after	hrs.
NW ¼ SE ¼ Section 22 T. 35 S R. 12 E W.M.	Artesian flow 2800 g.p.m. Date Augus	t 15,	1964
Bearing and distance from section or subdivision corner	Temperature of water 58 Was a chemical analysis a	made? 🔲 🖰	Yes 🗶 No
N 30° 45' W - 2705.3 from the SE cor.	(12) WELL LOG: Diameter of well below ca	sing 1	2
Sec. 22, T. 35 S., R. 12 E. W. M.	Depth drilled 956 ft. Depth of completed we		
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each c	the materi hange of	ial in each formation.
		11	
(3) TYPE OF WORK (check):	MATERIAL	FROM	TO
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	Rock	1 1	180
andonment, describe material and procedure in Item 12.	Clay Sondatone & hlock could	180	190
	Sandstone & black sand Broken lava	190 440	440
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Rock	495	<u>495</u> 505
Domestic A Industrial Municipal Rotary Driven Cable A Jetted	Clay	505	512
Irrigation ☐ Test Well ☐ Other ☐ Dug ☐ Bored ☐	Rock	512	530
(6) CASING INSTALLED: Threaded Welded	Clay	530	537
Threaded Welded W	Rock	537	710
	Clay	710	727
"Diam. from ft. to ft. Gage ft	Rock	727	803
	Clay	803	826
(7) PERFORATIONS: Perforated? ☐ Yes ■ No	Rock	826	925
Type of perforator used	Sand and cinders, red	925	956
Size of perforations in. by in.			
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.	4		
perforations from ft. to ft.			
perforations fromft. toft.			20
(8) SCREENS: Well screen installed? ☐ Yes ▼ No			
Manufacturer's Name		-	
Type			
	- More Ch.		
Diam Slot size Set from ft. to ft.		g. 15	1964
(9) CONSTRUCTION:		g. 17	19 64
	(13) PUMP:		
Well seal—Material used in seal Cement & Bentonite	Manufacturer's Name	••••••	
Depth of seal 495 ft. Was a packer used? No	Type:		
Diameter of well bore to bottom of seal	Water Well Contractor's Certification:		
Were any loose strata cemented off? 🗷 Yes 🔲 No Depth			
Was a drive shoe used? ■ Yes □ No	This well was drilled under my jurisdiction a	nd this	report is
Was well gravel packed? [] Yes [] NoSize of gravel:	true to the best of my knowledge and belief.		
Gravel placed fromft. toft.	NAME W. L. Hartley & Son (Person, firm or corporation) (Typ	•••••	•••••
Did any strata contain unusable water 🖸 🗋 Yes 🔳 No			
Type of water? depth of strata	Address Bonanza, Oregon		•••••
Method of sealing strata off	Drilling Machine Operator's License No1	19	
(10) WATER LEVELS:			•••••••
Static levelft. below land surface Date	[Signed] /s/ Robert F. Hartley (Water Well Contractor)		••••••
Artesian pressure lbs. per square inch Date	Contractor's License No. 164 Date Aug.	17	Ch
	DateAug.	 .L	., 1907