NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.



WATER WELL REPORT: OG State Well No. ...

STATE OF OREGON
(Please type or print)

State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount w lowered below static lev	ater level is
NameDept. of Agriculture-Forest Service	Was a pump test made? Yes No If yes, by whom	et
Address Deschutes National Forest	Yield: 50 gal./min. with no ft. drawdown	
Bend, Oregon.	" "	"
(2) LOCATION OF WELL:	" " "	,,
County Klamath Driller's well number 265	Bailer test gal./min. with ft. drawdow	vn after hra
14 14 Section 23 T. 238 R. 6E W.M.	Artesian flow g.p.m. Date	
Bearing and distance from section or subdivision corner	Temperature of water 40 Was a chemical analysis m	
	(12) WELL LOG: Diameter of well below casi	ing 8
Sunset Cove Campground	Depth drilled 181 ft. Depth of completed well	181 f
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of th stratum penetrated, with at least one entry for each characteristics.	and structure, an
	stratum penetrated, with at least one entry for each cho	inge of formation
(2) TYPE OF WORK (AL-AL)	MATERIAL	FROM TO
(3) TYPE OF WORK (check):	Pumice-Yellow-Brown Soft.	0 7
New Well Deepening Reconditioning Abandon	Sand & Gravel-Medium	7 12
pandonment, describe material and procedure in Item 12.	Basalt-Hard Grey	$\begin{array}{c c} 7 & 12 \\ 12 & 21 \end{array}$
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Red Cinders-Semi-hard	21 52
Domestic ☐ Industrial ☐ Municipal ☐ Rotary ☐ Driven ☐	Basalt-Hard Red Cinders-Semi- hard	52 5 9 59 181
Irrigation	Tod Olikola-John- Haid	09 101
# Diam. from O ft. to 20 ft. Gage 277		
6 "Diam. from 16 ft. to 181 ft. Gage 380		
(7) DEDECD ARIONS		
Teleplated, M. 163 [] No		
Type of perforator used Acetelyne Torch Size of perforations 4 in. by 6 in.		
Size of perforations 4 in, by 0 in. perforations from ft. to ft.		
98 perforations from 159 ft. to 181 - It.	Lowered 6"liner inwell 165"	
perforations from ft. to ft.	-onorog o renor runeer 100	
perforations from ft. to ft.		
perforations from ft. to ft.		,
(8) SCREENS: Well screen installed? ☐ Yes ℤ No		
Manufacturer's Name		
e		
am. Slot size Set from ft. to ft.	Wash	
Diam. Slot size Set from ft. to ft.		£-67 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 3-5-67 (13) PUMP:	19
Well seal—Material used in seal Bentonite	(10) 1 OMI.	
Depth of seal 20 ft. Was a packer used? no	Manufacturer's Name	**********************
Diameter of well bore to bottom of seal 16 in.	Type: H.F	>
Were any loose strata cemented off? \(\sum \) Yes \(\sum \) No \(\text{Depth} \)	Water Well Contractor's Certification:	
Was a drive shoe used?	This well was drilled under my jurisdiction and	3 47 4
Was well gravel packed? Yes No Size of gravel:	true to the best of my knowledge and belief.	a this report is
Gravel placed from ft ft	NAME CULLETT BROTHERS	
Did any strata contain unusable water? 🗌 Yes 🙀 No	(Person, hirm on corporation) (Type	or print)
Type of water? depth of strata	Address Route 1-Myrtle Creek, Ore.	*************************
Method of sealing strata off	Drilling Machine Operator's License No. 288	3
(10) WATER LEVELS:	machine Operator's License No.	
Static level 132 ft. below land surface Date 3-3-67	[Signed]	4
Artesian pressure Ibs. per square inch Date	Contractor's Ligense No. 252 Date 4-1-67	U
(USE ADDITIONAL SH	EETS IF NECESSARY	19
	- The Control of the	