WATER WELL REPORT STATE OF OREGON

KLANI 92 PLEASE TYPE ONA

JUL 29 1983 State Permit No.

	•
State Permit No.	**************************

	SALEM ORFGON	
Ī	(10) LOCATION OF WELL.	

(1) OWNER:	(10) LOCATION OF WELL:	
Name Ralph & Lois Smith	County Klamath Driller's well:	number
Address P.O. Box 26	NE 4 SE 4 Section 15 T. 36 S	
City Sprague River State OR 97639	Tax Lot # Lot Blk	Subdivision
2) TYPE OF WORK (check):	Address at well location: Sprague River,	off of Squaw Flat
New Well ☑ Deepening □ Reconditioning □ Abandon □	Road	
if abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	<u>3</u> 85 ft.
	Static level 85 ft. below la	ind surface. Date 6-20-83
Rotary Air 💢 Driven 🗌 Domestic 🗍 Industrial 🗎 Municipal 🗍 Rotary Mud 🗍 Dug 🔲 Irrigation 🗖 Test Well 🗎 Other 🗎	Artesian pressure lbs. per	r square inch. Date
Bored	(12) WELL LOG: Diameter of well below of	casing 16"
(5) CASING INSTALLED: Steel Plastic	I .	completed well 912 ft.
(5) CASING INSTALLED: Steel \(\text{\text{\$\mathbb{R}\$}} \) Plastic \(\text{\$\mathbb{T}\$} \) Threaded \(\mathbb{D} \) Welded \(\mathbb{R} \)	Formation: Describe color, texture, grain size and stru-	cture of materials; and show
16. "Diam from +1 ft to 129 ft Gauge 250	thickness and nature of each stratum and aquifer penet for each change of formation. Report each change in p	rated, with at least one entry
" Diam. from	and indicate principal water-bearing strata.	osition of Static water Level
LINER INSTALLED:	MATERIAL	From To SWL
	Sandy Top Soil	0 2
	Cemented Gravel	
(6) PERFORATIONS: Perforated? ☐ Yes ⋈ No		
Type of perforator used	Yellow Clay	
in. by in.	Blue Clay Black Sandstone	42 64 64 68
perforations from ft. to ft.		
perforations from	Blue Clay	68 85
perforations from ft. to ft.	Black Sandstone	85 89
(7) SCREENS: Well screen installed? Yes X No	Blue Clay	89 275
Manufacturer's Name	Black Sandstone	275 296
Type	Blue Clay Black Sandstone	296 385 385 399 85 '
Diam. Slot Size Set from ft. to ft.	Blue Clay	385 399 85 ' 399 434
Diam. Slot Size Set from ft. to ft.	Black Rock	434 450
December is a second and in Lord in Lo	Blue Clay	450 499
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Black Sand	499 505 85'
s a pump test made? 🕱 Yes 🗆 No If yes, by whom? Interstate	Black Rock	505 513
rield: 1050 gal./min. with 95 ft. drawdown after 11 hrs.	Black Sandstone	513 563
	Blue Clay	563 577
Air test gal./min. with drill stem at ft. hrs.	Black Rock	577 589
Bailer test gal/min. with ft. drawdown after hrs.	Red Lava Rock	589 630
tesian flow g.p.m.	Continued on another sheet	<u> </u>
remperature of water 54 Depth artesian flow encountered ft.	Work started 5-18 19 83 Completed	d 6-22 1983
9) CONSTRUCTION: Special standards: Yes □ No ☑	Date well drilling machine moved off of well	6-22 1983
Well seal—Material used Cement & 5% Bentonite	(unbonded) Water Well Constructor Certific	<u> </u>
Well sealed from land surface to 85 ft.	This well was constructed under my direct su	
Diameter of well bore to bottom of seal20 in.	and information reported above are true to my be	est knowledge and belief.
Diameter of well bore below seal16 in.	[Signed]	Date, 19
Number of sacks of cement used in well seal 40 sacks	Bonded Water Well Constructor Certification	
How was cement grout placed? Pumped	Bond 208 211 34 Issued by: Wester	
	(number) Suret	ty Company Name
	This well was drilled under my jurisdiction the best of my knowledge and belief.	and this report is true to
Vas pump installed?NO	Name Norm Sevey Well Drilling.	Tnc.
Was a drive shoe used? ☐ Yes ☑ No Plugs Size: location ft.	(Person, firm or corporation)	(Type or print)
Did any strata contain unusable water? ☐ Yes ☒ No	Address 800 Old Midland Rd. Kla	mhath Falls, OR
Type of Water? depth of strata	[Signed] Marson & live.	
Method of sealing strata off	Water Well Constructo	or
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	Date6	-24 , 19 83
Gravel placed from		

WATER WELL REPORT

STATE OF OREGON

RECEIVED

State Well No.

PLEASE TYPE OWNTER NESOURCES DEPT Permit No. SALEM. OREGON

(1) OWNER: Continued from other sheet:	(10) LOCATION OF WELL:			
Name Ralph & Lois Smith	County Klamath Driller's well number			
Address P.O. Box 26	NE 4 SE 4 Section 15 T. 36 S R.	10 E W.M		
City Sprague River State OR 97639	Tax Lot # Lot Blk	Subdivision		
(2) TYPE OF WORK (check):	Address at well location: Sprague River, Of	f of Squaw Fla		
New Well □ Deepening □ Reconditioning □ Abandon □	Road			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	385 ft		
		urface. Date 6–20–8		
Rotary Air Driven Domestic Dindustrial Municipal Rotary Mud Dug Dirrigation Dest Well Dother	Artesian pressure lbs. per squ	are inch. Date		
Bored . Thermal: Withdrawal . Reinjection .	(12) WELL LOG: Diameter of well below casin	g 16"		
(5) CASING INSTALLED: Steel	Depth drilled 912 ft. Depth of completed well 912 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
LINER INSTALLED:	MATERIAL Fro	om To SWL		
ft. Gauge	Continued:			
(6) PERFORATIONS: Perforated? ☐ Yes ☐ No		30 688		
Type of perforator used	Blue Clay with Streaks of			
Size of perforations in. by in.		88 877		
perforations from ft. to ft.	Soft Black Lava Rock 8	77 912		
perforations from				
perforations from ft. to ft.				
(7) SCREENS: Well screen installed? ☐ Yes ☐ No				
Manufacturer's Name				
Type				
Diam. Slot Size Set from ft. to ft.				
Diam. Slot Size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
s a pump test made? Yes No If yes, by whom?				
rield: gal./min. with ft. drawdown after hrs.				
!! " " " " " " " " " " " " " " " " " "				
Air test gal./min. with drill stem at ft. hrs.				
Bailer test gal./min. with ft. drawdown after hrs.				
tesian flow g.p.m.				
remperature of water Depth artesian flow encountered ft.	Work started 5-18 1983 Completed	6-22 19 8		
(9) CONSTRUCTION: Special standards: Yes □ No □	Date well drilling machine moved off of well	6-22 19 8		
Well seal—Material used	(unbonded) Water Well Constructor Certificati	on (if applicable):		
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used			
Diameter of well bore to bottom of sealin.	and information reported above are true to my best l	•		
Diameter of well bore below seal in.	[Signed] Da	te, 19		
Number of sacks of cement used in well seal sacks	Bonded water wen constitution Certification.			
How was cement grout placed?	Bond 208 211 34 Issued by: Western Surety Co. Surety Company Name			
	This well was drilled under my jurisdiction and			
777 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	the best of my knowledge and belief.	-		
Was pump installed?	Name	Name Norm Sevey Well Drilling, Inc. (Person, firm or corporation) (Type or print)		
Was a drive shoe used? ☐ Yes ☐ No Plugs	cafe [77 Red Free [5:40 FIG 008	th Falls. OR		
Type of Water? depth of strata	71			
Method of sealing strata off	[Signed] Water Well Constructor			
Was well gravel packed? ☐ Yes ☐ No Size of gravel:				
Gravel placed from				