| ORIGINAL File Original and WATER W  | ELL REPORT State Well No. 36/// -/40 //)   |
|---|--|
| Duplicate with the  | F OREGON G-4599 G1255 State Permit No. G1156   |
| (1) OWNER: Name EDW/N K. VIEIRA   | (11) WELL TESTS: Drawdown is amount water level is lowered below static level  |
| Address Box 136   | Was a pump test made? ☐ Yes No If yes, by whom?  |
| BEATTY OREGON   | Yield: gal./min. withft. drawdown after hrs.   |
| (2) LOCATION OF WELL:   | " " " "  |
| County KLAMATH Owner's number, if any—  | Bailer test gal./min. with ft. drawdown after hrs.   |
| 5. W. 1/4 5, E. 1/4 Section 14 T. 36.5 R. 1/E W.M.  | Artesian flow 1060 g.p.m. Date 7-69  |
| Bearing and distance from section or subdivision corner   | Temperature of water 8 Was a chemical analysis made?   Yes No  |
| Harting from the S. W. corner of the  | (12) WELL LOG: Diameter of well  |
| north 649 let.  | Depth drilled 5 8 0 ft. Depth of completed well 5 8 0 ft.  |
|   | Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each structure negative and with at latter that the third and pattern of the material in each   |
|   | MANUAL TO THE STATE OF THE STAT |
| 3) TYPE OF WORK (check):  | MATERIAL FROM TO   |
| New Well Deepening ☐ Reconditioning ☐ Abandon ☐   | Charles 180  |
| If abandonment, describe material and procedure in Item 11.   | black sand 80 140  |
| (4) PROPOSED USE (check): (5) TYPE OF WELL:   | chalk 140 290  |
| Pomestic   Industrial   Municipal   Rotary   Driven   | red Ina rock 290 380   |
| rrigation ☐ Test Well ☐ Other ☐ Cable ☐ Jetted ☐ Dug ☐ Bored ☐  | - pand stare 390 460   |
| (6) CASING INSTALLED: Threaded Welded   | love soch hardt blue 460 580   |
| "Diam. from ft. to 55 ft. Gage 188  |  |
| ft. to  |  |
| " Diam. from ft. Gage   |  |
| (7) PERFORATIONS: Perforated?   |  |
| Type of perforator used   | DECEIVED   |
| SIZE of perforations in by in the summer of | MAP 7 1958   |
| perforations fromft. toft.  | WAIT   |
| perforations fromft. toft.  | STATE ENGINE   |
| perforations fromft. toft.  | SALEM, UK-GON  |
| perforations from ft. to ft.  |  |
| (8) SCREENS: Well screen installed    Yes No  |  |
| Type Model No.  |  |
| Diam. Slot size Set from ft. to ft.   |  |
| Diam. Slot size Set from ft, to ft.   | Work started Dec 19 . Completed Lell, 19   |
| (1) CONSTRUCTION:   | (13) PUMP:   |
| Was well gravel packed? 🗆 Yes 🔊 No Size of gravel:  | Manufacturer's Name  |
| Gravel placed fromft. toft.   | Type: H.P.   |
| Was a surface seal provided? Yes □ No To what depth? / O ft.  Material used in seal—  |  |
| Did any strata contain unusable water?   Yes No   | Well Driller's Statement:  This well was drilled under my jurisdiction and this report is  |
| Type of water? Depth of strata  | true to the best of my knowledge and belief.   |
| Method of sealing strata off Comment  | NAME W. L. Harthey & Som   |
| (10) WATER LEVELS:  | (Person, firm, or corporation) Type or print)  |
| Static level ft, below land surface Date  Artesian pressure / P lbs per square inch. Date   | Address Dananja Ove  |
| ibs. per square men. Date 7 400 4   | Driller's well number  |
| Log Accepted by:  | [Signed] Thatley   |
| [Signed] Elvi A. Villa Date 23 Feb., 1958   | Licenso No / 6 4 (Well Driller)  |
| ,,  | License No. 125 J. Date 7 195 J.   |
| (USE ADDITIONAL SHEETS IF NECESSARY)  |  |