NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.



WATER

36/11-35

G-4538 State Permit No. (11) WELL TESTS: Drawdown is amount water level is lowered below static level level below static level is lowered below static level in the lowered below static level is lowered below static level in the lowered below static level is lowered by the lowered below static level is lowered by the lowered below static level is lowered by the lowered by t (1) OWNER: Mark Time Inc. Name gal./min. with 90 Yield: 3200 Star Rt. Box 1 ft. drawdown after Address Beaty, Oregon (2) LOCATION OF WELL: Bailer test ft. drawdown after gal./min. with hrs. County Klamath Driller's well number Artesian flow g.p.m. Date R. 11 E 34 S.E. 14 Section 35 T. 36 Temperature of water 53 Was a chemical analysis made?

Yes No Bearing and distance from section or subdivision corner (12) WELL LOG: Diameter of well below casing ft. Depth of completed well 384 Depth drilled 384 Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation. MATERIAL FROM O Black Soil (3) TYPE OF WORK (check): L 10 Hard Pan New Well Reconditioning [Deepening [Abandon [7] White halk 10 30 If abandonment, describe material and procedure in Item 12. 30 Sandstone (5) TYPE OF WELL: PROPOSED USE (check): 45 70 Blue Clay ☐ Driven ☐ Rotary 70 112 Domestic | Industrial | Municipal | Gritty Blue Clay Cable 112 Irrigation Test Well Other 125 Hard Blue Clay ☐ Bored Dug 125 Pummice Stone 131 (6) CASING INSTALLED: Threaded 131 196 Soft Black Sandstone Packed Sand (sandstone) 196 199 "Diam, from ft. to ft. Gage 199 244 Soft andstoneft. Gage Hard Black Sandstone 2111 260 Hard Brown Sandstone 260 290 (7) PERFORATIONS: Perforated?

Yes 290 Yellow Clay containing Pummice 305 Type of perforator used 305 Yellow Clay With Gravel 318 Size of perforations in. by 318 326 Hard Gray Sandstone perforations from ft. to ft. 326 328 Hard Cemented Gravel ... perforations from ft. to ft. 328 Hard Gray Rock perforations from ft. to ... 347 349 Cemented Gravel 352 349 loose Gravell perforations from ft. to ft. Extra Hard Black Rock 352 383 Loose Gravel With lots of water 383 (8) SCREENS: Well screen installed Manufacturer's Name Model No. Completed Nov. 30 ₁₉ 62 Work started Nov. 1 19 62 Slot size _____ Set from ____ ft. to ____ ... Slot size Set from ft. to Date well drilling machine moved off of well 19 62 (9) CONSTRUCTION: (13) PUMP: Well seal-Material used in seal Drive Shoe Driven in clay Manufacturer's Name Depth of seal 120 ft. Was a packer used? No Diameter of well bore to bottom of seal _____16____in. Water Well Contractor's Certification: Were any loose strata cemented off?
Yes No This well was drilled under my jurisdiction and this report is Was a drive shoe used? X Yes □ No true to the best of my knowledge and belief. Was well gravel packed? [Yes Ano Size of gravel: .. NAME Oren L. Storey Welldrilling
(Person, firm or corporation) (Type or print) Gravel placed from ft. to Did any strata contain unusable water? 🗖 Yes 🛂 No Address Box 347 Dorris, Calif. Depth of strata Type of water? Method of sealing strata off Drilling Machine Operator's License No. 11 (10) WATER LEVELS: ft. below land surface Date 11230/62 Static level 31 (Water Well Contracto 194 lbs. per square inch Date Artesian pressure Contractor's License No.