## WATER WELL REPORT STATE OF OREGON

KLAM 2034

## RECEIVED

Ω1

State Well No.

365/12F-20

MAR 18 1981

WATER SOURCES DEPT SALEM. OREGON

(1) OWNER: PAGE 1. Continued on another shee	<sup>t</sup> (10) LOCATION OF WELL:		
Name Bert Goff	County Klamath Driller's well number		
Address P.O. Box 142		2 E. W.M.	
City Beatty, OR, 97621 State ORECON	Tax Lot # Lot Blk Sul	bdivision	
(2) TYPE OF WORK (check):	Address at well location:		
New Well   Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
	Depth at which water was first found 55 95	ft.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level + ft. below land surface	e. Date	
y Air Driven Domestic X Industrial Municipal	Artesian pressure 2 lbs. per square in	nch. Date 3,14,81	
Rotary Mud   Dug   Irrigation   Test Well   Other   Cable   Bored   Thermal: Withdrawal   Reinjection	(12) WELL LOG: Diameter of well below casing	8 inch	
(5) CASING INSTALLED: Steel  Plastic	Depth drilled 613 ft. Depth of completed	640	
(5) CASING INSTALLED: Steel Threaded Welded Welded M.  8" Diam. from	Formation: Describe color, texture, grain size and structure of n thickness and nature of each stratum and aquifer penetrated, wit for each change of formation. Report each change in position of and indicate principal water-bearing strata.	naterials; and show h at least one entry	
LINER INSTALLED:	MATTERIAL		
none Diam from	MATERIAL From 0	To SWL	
ft. Gauge	Brown claystone 4	6	
(6) PERFORATIONS: Perforated? ☐ Yes 🖔 No	Sandstone 6	10	
Type of perforator used	Yellow clay 10	15	
Size of perforations in. by in.	Sandy blue clay 15	17	
perforations from ft. to ft. to ft.	Blue clay 17	25	
perforations from	Sandstone 25	30	
perforations from ft. to ft.	Brown clay & streaks of riolite 30	35	
(7) SCREENS: Well screen installed?   Yes  No	Sandstone 35	45	
Manufacturer's Name	Blue clay 45	95	
Type Model No.	Blue clay & streaks of sandstone95	140 + 2PSI	
Diam. Slot Size Set from ft. to ft.	Blue clay 140	160	
Diam. Slot Size Set from ft. to ft.	Blue claystone with layers of		
WELL TESTS:  Drawdown is amount water level is lowered	sandstone 160	180 + 2 PSI	
below static level	Blue clay 180	245	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	Soft riolite 245	280 + 2 PSI	
Yield: gal./min. with ft. drawdown after hrs.	Blue clay 280	295	
	Soft riolite 295	310	
Air test gal/min. with drill stem at ft. hrs.	Blue claystone 310	350	
Artesian flow 300 g.n.m.	Blue claystone with streaks of 350		
2.200Jan 110W 2	riolite	360	
		10, <sub>19</sub> 81	
(9) CONSTRUCTION: Special standards: Yes  No 🗓	Date well drilling machine moved off of well 3, 10,	19 81	
Well seal—Material used Coment	Drilling Machine Operator's Certification:		
Well sealed from land surface to60 ft.	This well was constructed under my direct supervision		
Diameter of well bore to bottom of seal12 in.	and information reported above are true to my best know		
Diameter of well bore below sealin.	[Signed] Driking Machine pperfor	3, 16,19 81	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 1388	***************************************	
How was cement grout placed? Pumped from the bottom of the seal up to the ground serface.	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this	report is true to	
Was pump installed? 10 Type HP Depth ft.	the best of my knowledge and belief.		
Was a drive shoe used? ☐ Yes 🍇 No Plugs Size: location ft.	Name Norm Sevey Well Drilling, Inc. (Person, firm or corporation)	(Type or print)	
Did any strata contain unusable water?   Yes  No	Address 5619 Leland Drive Klamath Fa	11s, OR.9760	
Type of Water? NONe depth of strata	$\mathcal{D}$		
Method of sealing strata off	[Signed] 408 (Water Well Contractor)	************	
Was well gravel packed? ☐ Yes K No Size of gravel:	Contractor's License No. Date 3, 16,	19.81	
Gravel placed from			

## ~WATER WELL REPORT STATE OF OREGON

RECEIVED
MAR 18 1981
State Well No. 3/3/12 F-20

WATER RESOURCES DEP Permit No. SALEM. OREGON

·			
(1) OWNER: PAGE 2. Continued from page 1.	(10) LOCATION OF WELL:	-	
Name Bert Goff	County Klamath Driller's well number		
Address P.O. Box 142	4 4 Section T.		_
City Beatty, OR. 97621 State Oregon	Tax Lot # Lot Blk	R. W. Subdivision	. <u>M.</u>
	Address at well location:	Buodivision	<u> </u>
(2) TYPE OF WORK (check):	Takin cos at well location.		_
New Well □ Deepening □ Reconditioning □ Abandon □  If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found		ft.
	Static level ft. below le	and surface. Date	
Air   Driven   Domestic   Industrial   Municipal   Rotary Mud   Dug   Irrigation   Test Well   Other	Artesian pressure lbs. per square inch. Date		
Cable   Bored   Thermal: Withdrawal   Reinjection	(12) WELL LOG: Diameter of well below	casing	
(5) CASING INSTALLED: Steel   Plastic			ft.
(5) CASING INSTALLED: Steel  Plastic  Threaded  Welded	Formation: Describe color, texture, grain size and stru	cture of materials: and sho	OW/
" Diam. from	thickness and nature of each stratum and aquifer pene	trated, with at least one ent	trv
"Diam from	for each change of formation. Report each change in p and indicate principal water-bearing strata.	osition of Static Water Ley	vel
LINER INSTALLED:			_
	MATERIAL	From To SWL	
ft. Gauge	CONTINUED FROM PAGE 1.		
(6) PERFORATIONS: Perforated?   Yes   No	Brown claystone	360 390 + 2 I	<u>PS</u> I
Type of perforator used	Black riolite rock (hard)	390 460	
Size of perforations in. by in.	Soft riolite rock	460 475	
perforations from ft. to ft.	Rielite rock (hard)	475 500	_
perforations from	Softer riolite rock	500 510	
perforations from	Black rock	510 613 + 2 F	PSI
(7) SCREENS: Well screen installed?   Yes   No			
Manufacturer's Name			_
Type	Artesian		
	-		
Diam. Slot Size Set from ft. to ft.  Drawdown is amount water level is lowered			
below static level			_
Was a pump test made? ☐ Yes ☐ No If yes, by whom?			
Yield: gal/min. with ft. drawdown after hrs.			_
Air test gal./min. with drill stem at ft. hrs.			
test gal/min. with ft. drawdown after hrs.			
Artesian flow g.p.m.			<del>-</del> -
Temperature of water Depth artesian flow encountered ft.	Work started 3, 3, 1981 Complete	d 3, 10, 19 8	$\bar{81}$
9) CONSTRUCTION: Special standards: Yes \( \text{No} \) No \( \text{No} \)	Date well drilling machine moved off of well 3.	10, 19 8	
Well seal—Material used	Drilling Machine Operator's Certification:		_
Well sealed from land surface to ft.	This well was constructed under my direct su	merwision Meterials use	
Diameter of well bore to bottom of sealin.	and information reported above are true to my be	st knowledge and belief	su E.
Diameter of well bore below sealin.	[Signed] (Drilling Machine Operator)	<sub>Date</sub> 3,16, <sub>19</sub> 81	
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No.		
low was cement grout placed?	Diffing Wacrane Operator's License No		_
The second secon	Water Well Contractor's Certification:		
and the second s	This well was drilled under my jurisdiction and this report is true to		
Vas pump installed? Type HP Depth ft.	the best of my knowledge and belief.		
Was a drive shoe used? ☐ Yes ☐ No Plugs Size; location ft.	Name Norm Sevey Well Drilling, Inc.  (Person, firm or corporation) (Type or print)		
Did any strata contain unusable water? ' Yes No	Address 5619 Leland Dr. Klamath	Falls. OR. 976	501
ype of Water? depth of strata			
Method of sealing strata off	[Signed] / aun Wee (Water Well Contracto	r)	
Vas well gravel packed? ☐ Yes ☐ No Size of gravel:	Contractor's License No408 Date	3. 16. 1981	Ĺ
ravel placed fromft. toft.			••