## WATER WELL REPORT STATE OF OREGON

## RECEIVED

State Well No. 365/125/4(C

MAY 9 1984 State Well No. 365/12E-140

MAY 9 1984 State Well No. 365/12E-140

PLEASE TYPE or PRINTING OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name DONNA PERRY	County KLAM ATH Driller's well number —
Address P.O.BOX 25	SW 4 SW 4 Section 14 T. 365 R. 12 E W.M.
City BEATTY State ORE	Tax Lot # Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location: BEATTY STORE
New Well Deepening Reconditioning Abandon A	(11) WATERD LIESVEN CO., L. J. J.
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 60 ft.
	Static level ft. below land surface. Date 4///
Rotary Air  Priven  Domestic  Mindustrial  Municipal   Rotary Mud  Dug   Irrigation  Test Well  Other	Artesian pressure lbs. per square inch. Date
☐ Bored ☐ Thermal: Withdrawal ☐ Reinjection ☐	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel  Plastic .	Depth drilled /60 ft. Depth of completed well /60 ft.
(5) CASING INSTALLED: Steel X Plastic  Threaded  Welded X	Formation: Describe color, texture, grain size and structure of materials; and show
Diam. from	thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level
13. 13. Diam. from 1 ft. to 17. 12. ft. Gauge 2.5.	and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
	BROWN SANDY SOIL 0 4
	PUMICE & LAUA 4 40
(6) PERFORATIONS: Perforated?   No	green Shalf 4060
Type of perforator used	Pumice 100 70
Size of perforations in. by in.	Black Ash 7075
perforations from	Pumice 25 82
perforations from	areen Shale 8282
perforations from ft. to ft.	Black Ash 8790
(7) SCREENS: Well screen installed?   Yes Tho	aray shalf. 80 100
Manufacturer's Name	7.50
Type Model No.	
Diam. Slot Size Set from ft. to ft.	
Diam. Slot Size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered	
below static level	
Wes a pump test made?   Yes No If yes, by whom?	
d: gal/min. with ft. drawdown after hrs.	
Air test 90 gal./min. with drill stem at 100 ft. / hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
Perature of water 57 Depth artesian flow encountered ft.	Work started 4/9 1984 Completed 4/// 1984
(9) CONSTRUCTION: Special standards: Yes 🗆 No	Date well drilling machine moved off of well 4/// 1984
Well seal—Material used Cement + 570 Bent	(unbonded) Water Well Constructor Certification (if applicable):
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of sealin.	and information reported above are true to my best knowledge and belief.
Diameter of well bore below sealin.	[Signed] Date 7/16, 1984
Number of sacks of cement used in well seal 197. 1.46 BeNT sacks	Bonded Water Well Constructor Certification:
How was cement grout placed?	Bond Issued by:
	(number) Surety Company Name
<i>1/ 2</i>	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was pump installed?	Name EESTORE ITSON WULL BRILL 1144 INC (Person, firm / corporation) (Type or print)
Was a drive shoe used? Yes No Plugs Size: location ft.	(Person, firm of corporation) (Type or print)
Did any strata contain unusable water? Yes \( \simeq \text{No} \)	Address 3847 HODE WILLMATH FALLS ORE
Type of Water? SURFACE depth of strata 14-40	[Signed] 6 Colority
Method of sealing strata off CAS/N94 CEMEN/	Water Well Constructor
Was well gravel packed? ☐ Yes Size of gravel:	Date, 19, 19
Graver praced HUIII	