NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER WELL REPORT

WA'TER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion. 6-10934?

## STATE OF OREGON

(Please type or print)

(Do not write above this line)

533-2471	tate Well No.	36s/	DE-1	lade
· //	tate Permit N	Го		

(1) OWNED.	(10) TOGETHOUSE OF THE		
(1) OWNER:	(10) LOCATION OF WELL:		
Name TERRY HAGER Address Box 85	County KLAMATh Driller's well number		
REATTY ORC	SW 4SE 4 Section 6 T. 36S R. 12E W.M.		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner		
New Well ☐ Deepening ☐ Reconditioning ☑ Abandon ☐			
If abandonment, describe material and procedure in Item 12.	(11) 11/4 (11/4)		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.		
Retary M Driven D	Depth at which water was first found ft.		
Domestic   Industrial   Municipal	Static level ft. below land surface. Date		
	Artesian pressure 20 lbs. per square inch. Date 5/14/80		
(5) CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing		
L'NER	Depth drilled ft. Depth of completed well ft.		
Diam. from	Formation: Describe color, texture, grain size and structure of materials;		
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer cenetrated, with at least one entry for each change of formation. Report each change in		
(6) PERFORATIONS: Perforated? Yes   No.	position of Static Water Level and indicate principal water-hearing strata.		
Type of perforator used	MATERIAL From To SWL		
Size of perforations in. by in.			
perforations from 1,3 ft. to 15			
# perforations from # # ft. to # 105 ft. # perforations from # # ft. to # 127 ft. # perforations from # # 108 ft. to # 127 ft.			
perforations from ft. to 12.7 ft.			
(7) SCREENS: Well screen installed?   Yes No			
Manufacturer's Name	X		
Type			
Diam. Slot size Set from ft. to Diam. Slot size Set from ft. to ft. to			
Set non 11. tott	- WEIVEU		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	JUN 2 3 1980		
a pump test made? Yes No If yes, by whom?	RESOURCES DEPT		
Yield: gal./min. with ft. drawdown after hrs.	LEM, OREGON		
"AIRLIFT 1488 GPM @ 140" 8 "			
" " " " " " " " " " " " " " " " " " " "			
er test gal./min. with ft. drawdown after hrs.			
Arcesian flow 500 g.p.m.			
Temperature of water 5 / Depth artesian flow encountered ft.	Work started 5 / 3/8019 Completed 5 / 1/2 / 2019		
(9) CONSTRUCTION:	Date well drilling mackine moved off of well (5-116/19)19		
Well seal—Material used	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my direct supervision		
Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and belief.		
Diameter of well bore below seal in.	[Signed] The Merretty Date Inc 19 1080		
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)		
How was cement grout placed?	Drilling Machine Operator's License No		
A.	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? Tyes No Plugs Size: location ft.	tide to the best of my knowledge and belief.		
Did any strata contain unusable water?   Yes No	Name EESTO REYY SON WELL BELLING INC. (Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address 3847 Hof & KFALLS OPE		
Method of sealing strata off	[Signed] & & Warrier		
Was well gravel packed?   Yes   No Size of gravel:	[Signed]		
Gravel placed from ft. to ft.	Contractor's License No		
(USE ADDITIONAL SHI			