WATER WELL REPORT STATE OF OREGON

K 1 AM C

RECEIVED

JUL 21 1981

State Well No. 365/2F-22C

(1) OWNER:	(10) I OCATION OF WELL			
Name Kenneth Allison	(10) LOCATION OF WELL:			
Address 2028 Reclamation	County Klamath Driller's we			
City Klamath Falls State OR 97601		S R. 12 E W.M.		
	Tax Lot # Lot Blk	Subdivision		
(2) TYPE OF WORK (check): New Well Deepening □ Reconditioning □ Abandon □	Address at well location:			
New Well Deepening □ Reconditioning □ Abandon □ If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed v	11		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	142 ft.		
Rotary Air 🛛 Driven 🗆 Domestic 🗆 Industrial 🗆 Municipal 🗆		land surface. Date 7-7-81		
Rotary Mud Dug Irrigation X Test Well D Other		per square inch. Date		
		v casing 12* & 8"		
(5) CASING INSTALLED: Steel TX Plastic	Depth drilled 597 ft. Depth of	f completed well 597 ft.		
Threaded □ Welded ⊠ 12"Diam.from +1ft.to 277ft. Gauge .250	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry			
# TO: C	" for each change of formation, Report each change in	position of Static Water Level		
"Diam. from	and indicate principal water-bearing strata.			
LINER INSTALLED:	MATERIAL	From To SWL		
ft. Gauge	Sandy Top Soil	0 1		
(6) PERFORATIONS: Perforated? ☐ Yes ☒ No	Pumice & Gravel	1 19		
Type of perforator used	Brown Clay	19 36		
Size of perforations in. by in.	Blue Clay	36 41		
perforations from ft. to ft.	Yellow Clay & Pumice	41 50		
perforations from	Brown Sandstone	50 59		
perforations from	White Pumice	59 70		
	Brown Clay	70 76		
(7) SCREENS: Well screen installed? ☐ Yes ☒ No Manufacturer's Name	Cross or CT	76 81		
	Diack Saila	81 82		
Type	Blue Clay	82 139		
Diam. Slot Size Set from ft. to ft.	Black Cinder Rock	139 141		
	Blue Shale	141 142		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Blue Clay with Streaks of -			
Was a pump test made? No Yes No If yes, by whom? Valley Pump	White Pumice	142 168 23'		
d: 1500 gal/min. with 33 ft. drawdown after 1 hrs.	Blue Clay	168 210		
" " "	Brown Clay with Streaks of -			
Air test gal./min. with drill stem at ft. hrs.	Brown Sand	210 222 23'		
Bailer test gal./min. with ft. drawdown after hrs.	Blue Clay with Streaks of -			
Adasian flow g.p.m.	Black Sand	222 , 234 23'		
iperature of water 56 Depth artesian flow encountered ft.	Gontinued On Another Sheet Work started 6-8			
(9) CONSTRUCTION: Special standards: Yes □ No ☒				
Well seal—Material used	Date well drilling machine moved off of well	7-7 1981		
Well sealed from land surface to 276	Drilling Machine Operator's Certification:	_		
Diameter of well bore to bottom of seal 16	This well was constructed under my direct st and information reported above are true to my be	pervision. Materials used		
Diameter of well bore below seal 12 in.	[Signed] Stephen R. The day	St knowledge and belief.		
Number of sacks of cement used in well seal 94 sacks	(Drilling Machine Operator)	Date .12, 199.1		
How was cement grout placed? Pumped from bottom of	Drilling Machine Operator's License No.	1171		
casing up to the ground surface.	Water Well Contractor's Certification:			
······································	This well was drilled under my jurisdiction and this report is true to			
Was pump installed?NOTypeHPDepthft.	the best of my knowledge and helief			
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	Name Norm Sevey Well Drilling, (Person, firm or corporation)	4		
Did any strata contain unusable water?	Address 800 Old Midland Bd. Klama	uypeorprint) ath Falls. OR 97601		
Type of Water? depth of strata		**************************************		
Method of sealing strata off	[Signed] / Low Alves (Water Well Contracto			
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	Contractor's License No. 408 Date	7-9-81 10 81		
Gravel placed from ft. to ft.				

WATER WELL REPORT

STATE OF OREGON

RECEIVED JUL 2 1 1981

WATER RESOURCES DEPTtate Permit No.

	SALEM, OREGON		
(1) OWNER Continued from page 1	(10) LOCATION OF WELL:		
Name Kenneth Allison	a rrl amada		
Address 2028 Reclamation	County Klamath Driller's well E2 4 SW 4 Section 22 T. 36S	R. 12 E	
City Klamath Falls, State OR 97601	Tax Lot # Lot Blk	Subdivision	<u>W.M.</u>
(2) TYPE OF WORK (check):	Address at well location:	Subdivision	1
New Well □ Deepening □ Reconditioning □ Abandon □		····	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	æll.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found Static level 23 ft. below!	142	
Rotary Air Driven Domestic Industrial Municipal	Aud to		7-7-81
Rotary Mud	(40)	er square inch. Date	
(5) CASING INSTALLED: Steel	(12) WELL LOG: Diameter of well below Depth drilled 597 ft. Depth of Formation: Describe color, texture, grain size and strt thickness and nature of each stratum and aquifer pene for each change of formation. Report each change in and indicate principal water-bearing strata.	completed well ucture of materials;	597 ft.
LINER INSTALLED:	MATERIAL	From To	SWL
	Blue Clay	234 259	
(6) PERFORATIONS: Perforated? ☐ Yes ☐ No	Blue Clay with Streaks of -		
Type of perforator used	Black Sand	259 269	23'
Size of perforations in. by in.	Coarse Brown Sand	269 271	23'
perforations from ft. to ft.	Red Shale	271 274	
perforations from ft. to ft.	Sandy Brown Clay	274 279	
ft. to ft.	Red Lava Rock	279 285	23'
(7) SCREENS: Well screen installed? Yes No	Black Lava Rock	285 288	23'
Manufacturer's Name	Brown Lava Rock	288 300	23'
Type Model No.	Brown Sand Rock Red Lava Rock	300 312	23'
Diam. Slot Size Set from ft. to ft.	Brown Lava Rock	312 390	23'
<u>Diam.</u> Slot Size Set from ft. to ft.	Black Lava Rock	390 413 413 597	23'
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	1	71) 397	_23'
Was a pump test made? Yes No If yes, by whom?	Well is 12" to 373'then is 8" from 373' to 597'		
d: gal/min. with ft. drawdown after hrs.	18 0. 1LOW 3/3, 10 24/.		
Air test gal./min. with drill stem at ft. hrs.			
Bailer test gal./min. with drill stem at ft. hrs. Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.			
aperature of water Depth artesian flow encountered ft.			
(A) CONCUDITORION	Work started 6-8 19 81 Complete		19 8 1
- · · · · · · · · · · · · · · · · · · ·	Date well drilling machine moved off of well	7-7	19 <u>81</u>
Well seal—Material used	Drilling Machine Operator's Certification:		
Diameter of well bore to bottom of seal	This well was constructed under my direct su	pervision. Mater	ials used
Diameter of well bore below seal	and information reported above are true to my be	est knowledge and Date7.–9	d belief.
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)		•
How was cement grout placed?	Drilling Machine Operator's License No	1171	•••••
	Water Well Contractor's Certification:		
W	This well was drilled under my jurisdiction	and this report is	s true to
Was pump installed?	the best of my knowledge and belief. Name Norm Sevey Well Drilling, Inc.		
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes ☐ No	(Person, IIrm or corporation)	(Time on n	mint)
Type of Water? depth of strata	Address 800 Old Midland Rd. Klam	ath Falls,	OR 9760
Method of sealing strata off	[Signed] Lann Jlve (Water Well Contracto		
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contracto	r) 🕝 🔿	
Gravel placed from ft. to ft.	Contractor's License No. 408 Date	<i>(.</i> .У	,19¤l