NOTICE TO WATER WELL CONTRACTOR. The original and first copy of this report are to be filed with the water water well report.

WATER RESOURCES DEPARTMENT 12 1978 STATE OF OREGON SALEM, OREGON 97310 WIFT 12 1978 STATE OF OREGON (Please type or print) of well completion. TER RESOURCES (Do not write above this line)

CALEM. OREGUM	ΔPR 1 0 1078 Correcte	d by WKD Stail
(1) OWNER:	(10), LOCATION OF WELDEPT.	
Name U. E. Freid	County A A Complete Swell number	
Beath, Dec.	SW 1/4 LC 1/4 Section 2 5 To 65 R.	12E W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	7	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.	
Rotary Driven Domestic Industrial Municipal D	Static level 30 ft. below land surface	Poto 2-19.7
Cable	Artesian pressure lbs. per square inch	
CASING INSTALLED: Threaded Welded Welded Welded Threaded Threaded Welded Threaded T	(12) WELL LOG: Diameter of well below casing S Depth drilled 15.3 ft. Depth of completed well 15.3 ft.	
	Formation: Describe color, texture, grain size and str and show thickness and nature of each stratum and	aquifer penetrated
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. R position of Static Water Level and indicate principal v	eport each change in
Type of perforator used	MATERIAL From	To SWL
Size of perforations in. by in.	Brown shale 0	23
perforations fromft. toft.	Sandstone - Brown 23	35
perforations fromft. toft.	gray Clay 35	38
perforations fromft. toft.	Macdatan Slast 58	133
(7) SCREENS: Well screen installed? Yes No	on nowatory: - Training 83	86
Manufacturer's Name	sandstone- black 86	70
Type Model No.	CLAYGERY WITH BLACK GO	153
Diam. Slot size Set from ft. to ft.	SANT Stone	
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☐ Yes No If yes, by whom?		
Yeld: gal./min. with ft. drawdown after hrs.	* 1	
" " "		
" " "		
Bailer test 200 gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
perature of water 5 Depth artesian flow encountered ft.	Wash darks 2 28 78 7	1 2 2 4 6 6
	Work started 2 1978 Completed 2 Date well drilling machine moved off of well 3 -	1 60
(9) CONSTRUCTION:	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	19 /
Well seal-Material used C. Chi Ent	Drilling Machine Operator's Certification:	
Well sealed from land surface toft. Diameter of well bore to bottom of sealin.	This well was constructed under my direct supervision. Materials used and information reported above are true to my	
Diameter of well bore to bottom of seal	best knowledge and belief.	,
Number of sacks of cement used in well seal, sacks	[Signed] Marine Operator) Date 4 , 1975	
How was cement grout placed Milled in mest	Drilling Machine Operator's License No. 1095	
Casing till full	Water Well Contractor's Certification:	
X	This well was drilled under my jurisdiction and this report is	
Was a drive shoe used? Tyes No Plugs Size: location ft.	true to the best of my knowledge and belief	
Did any strata contain unusable water? Yes No	Name (Person, first or corporation) (Type or print)	
Type of water? depth of strata	Address BOX 237 BONANZA ORC	
Method of sealing strata off	[Signed] Sharon Tiene thather	
Was well gravel packed? ☐ Yes No Size of gravel:	(Water Well Contractor)	
Gravel placed from ft. to ft.	Contractor's License No. 62 Date	19.78