

NOTICE TO WATER WELL CONTRACTOR: The original and first copy of this report are to be filed with the

WATER WELL REPORT

KLAMATH 2090 RECEIVED

WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 within 30 days from the date of well completion.

MAY 12 1978

STATE OF OREGON (Please type or print) WATER RESOURCES DEPT. SALEM, OREGON

State Well No. 365/2E-250C State Permit No.

RECEIVED

APR 19 1978

(1) OWNER:

Name D.E. Field Address Sprague River Rd. Beatty, Ore.

(2) TYPE OF WORK (check):

New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven [ ] Cable [ ] Jetted [ ] Dug [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [X] Industrial [ ] Municipal [ ] Irrigation [ ] Test Well [ ] Other [ ]

(5) CASING INSTALLED:

8" Diam. from 1.5 ft. to 2.6 ft. Gage 250 Threaded [ ] Welded [X]

(6) PERFORATIONS:

Type of perforator used Size of perforations in. by in. Perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [ ] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [ ] Yes [X] No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs. Bailer test 200 gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Temperature of water 58 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement Well sealed from land surface to 26 ft. Diameter of well bore to bottom of seal 10 in. Diameter of well bore below seal 8 in. Number of sacks of cement used in well seal 16 sacks How was cement grout placed? Mixed in mixer and poured around casing till full Was a drive shoe used? [ ] Yes [X] No Plugs Size: location ft. Did any strata contain unusable water? [ ] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [ ] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL DEPT.

County ADAMS, OREGON Miller's well number SW 1/4 R. 25 T. 36S R. 12E W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 50 ft. Static level 30 ft. below land surface. Date 2-29-78 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Table with columns: MATERIAL, From, To, SWL. Rows include: Brown shale (0-23), Sandstone-Brown (23-35), Gray Clay (35-38), Brown Clay (38-58), Sandstone-Black (58-82), Sandstone-Brown (82-86), Sandstone-Black (86-90), Clay gray with black (90-153), Sand Stone.

Work started 2-28 1978 Completed 2-30 1978 Date well drilling machine moved off of well 3-1 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Sharon F. Hartley Date 4-18, 1978 (Drilling Machine Operator) Drilling Machine Operator's License No. 1095

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name Hartley Well Drilling (Person, firm, or corporation) (Type or print) Address Box 237 Bonanza, Ore [Signed] Sharon Irene Hartley (Water Well Contractor) Contractor's License No. 692 Date 4-18, 1978