NOTICE TO WATER WELL CONTRACTOR

Gravel placed from

The original and first confithis report are to be E C E

WELL REPORT

315 State Well No. 36/

filed with the
STATE ENGINEER, SALEM, OREGON filed with the engineer, salem, oregon wall 11 1908 (Please type or print) within 30 days from the date of well completion STATE ENGINEER write above this line)

State Permit No.

SALEM_CREGON	G5309	<u>well:</u>	<u>#2</u>	
(1) OWNER:	(11) LOCATION OF WELL:			
Name CARSON PMERKLEY	County KLANATA Driller's well n	umber		
Address POBOX 63 BLY, ORE.	SW 4 SE 4 Section 29 T. 3	SR. 14	E	W.M
	Bearing and distance from section or subdivision			
(2) TYPE OF WORK (check):				
New Well Deepening Reconditioning Abandon				
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well	below casing	18-16	-12
Rotary Driven Domestic Industrial Municipal	Depth drilled 485 ft. Depth of comp			ft
Dug	Formation: Describe color, texture, grain size			aterials
CASING INSTALLED: Threaded Welded Welded tt. to	and show thickness and nature of each strat with at least one entry for each change of for in position of Static Water Level as drilling pr	um and aqui nation. Repo	ifer pen ort each	netrated, change
18 " Diam. from + 1 ft. to 2 4 ft. Gage 250	MATERIAL	From	То	SWL
" Diam. from ft. to ft. Gage	TOD SOIL	0	2	
PERFORATIONS: Perforated? Yes No.	BROWN LAVA	2 /	14	
Type of perforator used	YELLOW ROCK		0	
Size of perforations in. by in.	BLACK BASALT		7	
perforations from ft. to ft.	BROWN LAVA	27 1	180	
perforations from ft. to ft.	BLACK BASALT		2/	
perforations from ft. to ft.	BROWN LAVA	1	4/	
perforations from ft. to ft.	BLACK BASALT		74	
perforations from ft. to ft.	BROWN LAVA		57 52	
(E) COPPENIA	BROWN SHALE		62	
(7) SCREENS: Well screen installed? Yes No	CLAY BOUND GRAVEL	1	95	
Manufacturer's Name	BROWN SHALE		143	
Type Model No.	BROWN LAVA		69	
Diam. Slot size Set from ft. to ft.	GRAY BASALT	469 4	12	
Diam. Slot size Set from ft. to ft.	BROWN CINDERS CAVING	472 4	85	
(8) WATER LEVEL: Completed well.				
Static level 42'6" ft. below land surface Date 7/3/68	18" to 150'	+		
esian pressure lbs. per square inch Date	16" to 473'			
(9) WELL TESTS: Drawdown is amount water level is lowered below static level	12" to 485"			
Was a pump test made? Yes \(\sigma \) No If yes, by whom? PUMD CENTER			7 0	
d: gal./min. with ft. drawdown after hrs.	Work started 5/7/68 19 Comple	ted 7/3	168	19
2300 " 108 " 3 "	Date well drilling machine moved off of well	7/3/1	68	19
" " " "	Drilling Machine Operator's Certification:			
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my d	lirect super	vision.	Mate-
	rials used and information reported abo knowledge and belief.	ve are tru	e to m	iy best
Artesian flow g.p.m. Date	Shilma Onin	Data 7/	9/68	·/
Temperature of water 58 Was a chemical analysis made? ☐ Yes No	[Signed] (Drilling Machine Operator)	Date	·/,	19
(10) CONSTRUCTION:	Drilling Machine Operator's License No.	110		
Well seal-Material used BENTIONITE				
Depth of seal	Water Well Contractor's Certification:			
Diameter of well bore to bottom of seal	This well was drilled under my jurisd true to the best of my knowledge and beli		this re	port is
Were any loose strata cemented off? Yes No Depth	NAME EESTOREY			
Was a drive shoe used? ▼Yes □ No	(Person, firm or corporation)	(Type of		••••••
Did any strata contain unusable water? Yes No	Address 3831 Hope AF	1225	ORC	o
Type of water? depth of strata	0 B 11h			
Method of sealing strata off	[Signed] Oodland			•
Was well gravel packed? Yes No Size of gravel:	(Water Well/Contra	ctor)	d	
Gravel placed from ft. to ft.	Contractor's License No Date	1/1/19	o.,	19