

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

KLAM 2151

KLAM 2151 WATER WELL REPORT

STATE OF OREGON (Please type or print)

(Do not write above this line)

RECEIVED DEC 8 1976

State Well No. 36S/14E-29bd State Permit No.

(1) OWNER:

Name WILBUR J. SMITH Address Box 133 BLY OREGON

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

(3) TYPE OF WELL:

Rotary [X] Cable [] Dug []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [X] Test Well [] Other []

CASING INSTALLED:

Threaded [] Welded [X] 16.00" Diam. from 10 to 37 ft. Gage 250

PERFORATIONS:

Perforated? [] Yes [X] No. Type of perforator used Size of perforations in. by in.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [X] Yes [] No If yes, by whom? INTERSTATE Yield: gal./min. with ft. drawdown after hrs. 2100 " 77 1/2 " 2 "

(9) CONSTRUCTION:

Well seal-Material used CEMENT Well sealed from land surface to 37 ft. Diameter of well bore to bottom of seal 20 in. Number of sacks of cement used in well seal 75 sacks Brand name of bentonite Number of pounds of bentonite per 100 gallons of water Was a drive shoe used? [X] Yes [] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Klamath Driller's well number SE 1/4 NW 1/4 Section 29 T. 36 S R. 14 E W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 100 ft. Static level 32 1/2 ft. below land surface. Date 11/11/76 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 15 1/4 200 Depth drilled 615 ft. Depth of completed well 615 Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include: BROWN CLAY TOPSOIL, YELLOW SHALE, CRICKET RED SHALE, BROWN SAND, BLACK BASALT, BROWN BROWN BASALT, BROWN BASALT, SHALY BASALT, BLACK BASALT, RED SHALY SAND, COMPACT BROWN SAND & LAVA, BROWN SHALE ROCK & STAGNANT PUMICE, BROWN SAND BROWN LAVA SAND, BROWN LAVA SHALE & PUMICE, BROWN SAND & PUMICE, BROKEN BROWN LAVA, BLACK BASALT, BROWN SHALE & PUMICE STAGNANT, BROWN LAVA, BLACK BASALT, BROKEN BLACK BASALT, BLACK BASALT.

Work started 10/20/76 19 Completed 11/11/76 19 Date well drilling machine moved off of well 11/11/76 19

Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] David M. Stroy Date 12/6, 1976 Drilling Machine Operator's License No. 656

Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name E.E. STURGEYSON WELL DRILLING INC. (Person, firm or corporation) (Type or print) Address 3247 HOPE K FALLS, ORE. [Signed] David M. Stroy (Water Well Contractor) Contractor's License No. 601 Date 12/6, 1976