NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

KLAM 2156 WATER WELL REPORMAY 181978 STATE OF OREGON (Please type or print)

State	well	No.	365/14E-3000
-------	------	-----	--------------

within 30 days from the date of well completion. (Please type (Please type)		No
(4) 0744777		
(1) OWNER:	(10) LOCATION OF WELL:	
Name RODNEY L. HADLEY	County Driller's well i	number
Address Box 3/2	NE 14NE 1/4 Section 30 T.36	S R. 14E V
BLY ORE	Bearing and distance from section or subdivis	
(2) TYPE OF WORK (check):	Bearing and distance from section of subdivis	aon corner
New Well □ Deepening ★ Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.		
	(11) WATER LEVEL: Completed v	vell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	,
Rotary Driven Domestic Industrial Municipal		
Cable Jetted		surface. Date 3/2/
e Bored Irrigation Test Well Other	Artesian pressure lbs. per squa	are inch. Date
) CASING INSTALLED: Threaded Welded	(10) 100	H
	(12) WELL LOG: Diameter of well	below casing
"Diam. from	Depth drilled 500 ft. Depth of comp	oleted well 500
	Formation: Describe color, texture, grain size	and structure of mater
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratu	ım and aquifer penetra
i) PERFORATIONS: Perforated? Yes No	with at least one entry for each change of form position of Static Water Level and indicate pri	-
Perforated? Yes No.	position of Blatic Water Bever and indicate pri	T i I
Type of perforator used	MATERIAL	From To SW
Size of perforations in. by in.		
perforations from ft. to ft.	REAMED 83/4 Bere	
perforations from ft. to ft.	TO12" BORE	48 141
perforations fromft, toft.	YYX BOBE	141 148
perforations from	X34 BORETO BOTTOM	148 500
(7) SCREENS: Well screen installed? Yes No	New Bore 3 70	2
Manufacturer's Name	GEMENTED PUMICE	370 380
Type		122
Diam. Slot size Set from ft. to ft.	BROWN LAVAC STREAKS OF FUND	T
Diam. Slot size Set from ft. to ft.	BROWNLAVA	482 500
Diani		
(8) WELL TESTS: Drawdown is amount water level is		
lowered below static level	11.0	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	Check PROJOUS LO	49
eld: gal./min. with ft. drawdown after hrs.		/
" " "	SENT IN SEPT 17	1
<i>II</i>		
Bailer test gal./min. with ft. drawdown after hrs.		
tesian flow g.p.m.		
mperature of water Depth artesian flow encountered ft.	Work started 3 //3/789 Complete	ted 3/2//78 19
		51.11.01
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3/4/1/78/19
Well seal—Material used	Drilling Machine Operator's Certification	: / /
Well sealed from land surface toft.	This well was constructed under my	direct supervisi
	Materials used and information reported	above are true to
Diameter of well bore to bottom of sealin.	best knowledge and belieff	- 4/11-/78
Diameter of well bore below seal in.	[Signed] (Drilling Machine Operator)	Date 7/15/1/3/9
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	115
Number of sacks of bentonite used in well seal sacks	Diffing Machine Operator & Interior 176.	
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons		liation and this war-
of water	This well was drilled under my jurisd true to the best of my knowledge and be	neuon and unis report lief.
Was a drive shoe used? Yes No Plugs Size: location ft.	LOW CAN MOI	LPRILL ING IL
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address 3847/ HODE K	FALLS OR
Method of sealing strata off	DE Street	
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Cont	ractor)
	111	4/15/78
Gravel placed from ft. to ft.	Contractor's License No	.ggftfgd. 19.