NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

## STATE OF OREGON

(Please type or print)

(Do not write above this line)

KLAM 2227

31	00	2211
State Well No.	15	a Dan

State Permit No. Loc corrected by WRD staff

(1) OWNER:	(10) LOCATION OF WELL:			
Name Jesperson - Edgewood		County KLAMATh Driller's well number 10		
Address RTD Box 8095	NW MW & Section 23 T. 375	R. E W.M.		
KLAMATA FALLS, QRE	Bearing and distance from section or subdivisi	on corner		
(2) TYPE OF WORK (check):				
New Well Deepening □ Reconditioning □ Abandon □				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	72 n.		
Rotary Driven Domestic Industrial Municipal	Static level 93 ft. below land s	surface. Date		
Bored   Irrigation Test Well Other	Artesian pressure lbs. per squar	e inch. Date		
'5) CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well it			
16 60 " Diam from 1t. to ft. Gage	Depth drilled 2000 ft. Depth of completed well 2000 ft.  Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in			
" Diam. from . # . ft. to . 4 . ft. Gage . 3.50				
?) PERFORATIONS: Perforated?   Yes No.	position of Static Water Level and indicate prin	cipal water-bearing strata.		
Type of perforator used	MATERIAL	From To SWL		
Size of perforations in. by in.	BROWN CLAY + BOULders	0 7		
perforations from ft. to ft.	BROWN SHALEY BOULDERS	7 14		
perforations from ft. to ft.	BROKEN BROWNLAVA	14 37		
perforations from ft. to ft.	BROWN SANDSTONE	122 200		
(7) SCREENS: Well screen installed?   Yes No	BROKEN CRAY LAVA	172 200 Fac		
Manufacturer's Name		' «·		
Type Model No				
Diam Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.	RACEVED			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	OCT - 9 1979			
Was a pump test made?  Yes No If yes, by whom?	WATER RESOURCES DEPT			
d: gal./min. with ft. drawdown after hrs.	SALEM, OREGON			
AIR LIFT 1000 6" PM + @ 200" 2 "				
Bailer test gal./min. with ft. drawdown after hrs.				
sian flow g.p.m.				
mperature of water Depth artesian flow encountered ft.	Work started \$1/5/79 19 Complete	ed 8/29/79 19		
(0) CONSTRUCTION.	Date well drilling machine moved off of well	8 130 /7919		
(9) CONSTRUCTION:  Well seal—Material used CEMENT	Delline Machine Operatoris Contillections	<del></del>		
	Drilling Machine Operator's Certification: This well was constructed under my	direct supervision.		
Well sealed from land surface to	Materials used and information reported			
Diameter of well bore below seal	best knowledge and belief.	20 201		
Number of sacks of cement used in well seal 72 sacks	[Signed] Machine Operator)	Date 1.0.1.8, 192.7.		
How was cement grout placed? Pumped	Drilling Machine Operator's License No	710		
	Water Well Contractor's Certification:			
	This well was drilled under my jurisdi	ction and this report is		
Was a drive shee wood? W. C. V. Diver	true to the best of my knowledge and beli	ief.		
Was a drive shoe used? Yes \( \subseteq No Plugs	Name EESTOREY & SOXWEL	LARILLINGING		
Did any strata contain unusable water?  Yes	Address 3847 Hop & All	(Type or bunt)		
Type of water? depth of strata	Address	××		
Method of sealing strata off	[Signed] (Water Well Control	<b>2</b>		
Was well gravel packed?   Yes No Size of gravel:	746	1/30/79 10		
Gravel placed from ft to ft	Contractor's License No. / Date /	/3 4// / 19		