NOTICE TO WATER WELL CONTRACTOR

## water resources department. Salem, Oregon 97310 within 30 days from the date of well completion. KLAM 2262 WATER WELL REPORT STATE OF OREGON (Please to be filed with the

State	Well No. 375/10E-8bc
State	Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	
Name Jes Person EDG e wood INC	County KLAMATh Driller's well n	umber
Address RT2 Box 8095	SW 14 NW 14 Section 8 T. 375	
ALAMATH FALLS, ONE	Bearing and distance from section or subdivisi	
(2) TYPE OF WORK (check):		
New Well Deepening Reconditioning Abandon		
If abandonment, describe material and procedure in Item 12.	· (11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	, ft
Rotary Driven Domestic Industrial Municipal	Static level // ft. below land	surface. Date 8/9
Cable   Jetted   Irrigation   Test Well   Other	Artesian pressure Ibs. per squar	re inch. Date
CASING INSTALLED: Threaded  Welded X	(12) WELL LOG: Diameter of well	below casing 15
"Diam. from ft. to ft. Gage  "Diam. from ft. t. to ft. Gage 250"	Depth drilled 192 ft. Depth of comp	eted well 187 ft
"Diam from ft. to ft. Gage"	Formation: Describe color, texture, grain size	
Diam. from It. to Gage	and show thickness and nature of each stratu with at least one entry for each change of forma	• • • • • • • • • • • • • • • • • • • •
Perforated? Tyes No.	position of Static Water Level and indicate prin	icipal water-bearing strata
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	BROWN SANDY 501L	0 2
perforations from ft. to ft.	BROWN LAVA ROCK	2 19
perforations from ft. to ft.	LIGHT BROWN CHALK ROCK	19 44
perforations from ft. to ft.		44 61
(7) SCREENS: Well screen installed?   Yes  No	BLACK SANDY JEALE RROKEN BROWN SANDSTONE	19 14
Manufacturer's Name		24 159
Type Model No	PANT DIVERY LYNGH WIS JOHN	159 162
Diam. Slot size Set from ft. to ft.	BROWN SANDSTONE	102 170
Diam. Slot size from ft. to ft.	BROWN SAND	770 177
(8) WELL TESTS: Drawdown is amount water level is	BRAY LAVA	177/10
lowered below static level	BROWN SANG	181 186
Was a pump test made?  Yes No If yes, by whom?	GRAY RA VA	192
d: gal./min. with ft. drawdown after hrs.	0.4070	
IR LIFT GOC"GPM+ @190" 3"	007 - 91979	
" " " "	WATER RESOURCES I	DEPT
Bailer test gal./min. with ft. drawdown after hrs.	SALEM, OREGON	
sian flow g.p.m.		
aperature of water Depth artesian flow encountered ft.	Work started 7/10/79 19 Complete	ed 8/9/79 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	8//5/79 19
Well seal-Material used CCMENT	Drilling Machine Operator's Certification:	/ /
Well sealed from land surface to ft.	This well was constructed under my	direct supervision
Diameter of well bore to bottom of seal 20 in.	Materials used and information reported best knowledge and belief.	above are true to my
Diameter of well bore below sealin.	[Signed] Like & Cherry	Date / C/8 1972
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	710
How was cement grout placed?	Drilling Machine Operator's License No.	
	Water Well Contractor's Certification:	
	This well was drilled under my jurisd	
Was a drive shoe used? ▼Yes □ No Plugs Size: location ft.	true to the best of my knowledge and bel	iei. Il AP.LL ING ING
Did any strata contain unusable water?   Yes	Name (Person, firm of corporation)	(Type or print)
Type of water? depth of strata	Address 3247HOPE X FALL	S. ORC
Method of sealing strata off	(Signed) & Ship	
Was well gravel packed?   Yes No Size of gravel:	[Signed] (Water Well Contr	actor)
Gravel placed from ft. to ft.	Contractor's License No Date	1/0/77 19