NOTICE TO WATER WELL CONTRACTOR The original and first copy

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

KLAM 2299 REGEIVED

STATE OF OREGON OCT 2 1 1974 State Well No. 375/11E-1

(Please type or print) STATE ENGINEER ate Permit No.
(Do not write above this lineSALEM, OREGON Klamath

6-7093

(1) OWNER:	(10) LOCATION OF WELL:
Name John Kemper	County Driller's well number
Address 4633 Rolando Drive	1/4 Section 1 T. 37 R. 11 E W.M.
Rolling Hill Estates, Ca. 90274	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 28 ft.
Rotary Driven Domestic Dindustrial Municipal Domestic Municipal Domestic Dindustrial Dindustr	Static level 20 ft. below land surface. Date
Cable □ Jetted □ Dug □ Bored □ Irrigation ▼ Test Well □ Other □	Artesian pressure Ibs. per square inch. Date
(5) CASING INSTALLED: Threaded □ Welded ♣	(12) WELL LOG: Diameter of well below casing 10
10 " Diam. from 0 ft. to 87 ft. Gage 250	Depth drilled 137 ft. Depth of completed well 137 ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
"Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
(6) PERFORATIONS: Perforated? X Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Factory	MATERIAL From To SWL
Size of perforations 1/4 in. by 21/2 in.	Top soil 0 2
perforations from 2.7 ft. to 8.7 ft.	Gravel & Clay 2 10
perforations fromft. toft.	Sandrock 10 68
perforations from ft. to ft.	Lava Rock (honey comb) 68 80
/// CODINENC.	Gray Lava 80 90,
(7) SCREENS: Well screen installed? Yes No	Red Lava (rock) 90 137
Manufacturer's Name	
Type Model No Diam Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
The state of the s	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	,
Was a pump test made? K Yes □ No If yes, by whom?Driller	
Wald: 475 gal./min. with 47 ft. drawdown after 4 hrs.	
" " "	
n " " " " " " " " " " " " " " " " " " "	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	,
Imperature of water Depth artesian flow encounteredft.	Work started 9/24 19 74 Completed 10/7 19 74
	Work started 9/24 19/4 Completed 10// 19/4 Date well drilling machine moved off of well 10/8 19/74
(9) CONSTRUCTION: Cement	
Well seal—Material used	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Well sealed from land surface toft.	Materials used and information reported above are true to my best knowledge and itslief.
Diameter of well bore to bottom of seal 14 in.	
Diameter of well bore below sealin. Number of sacks of cement used in well seal1sacks	[Signed] Law Coulor Date 10/15, 1974
	Drilling Machine Operator's License No. 342
Number of sacks of bentonite used in well seal sacks Brand name of bentonite	
Brand name of bentonite Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water lbs/100 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ★KYes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? TYes 17 No	Name .C. & C. Enloe Drilling (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address P. O. Box 323, Dorris, Ca. 96023
Method of sealing strata off	some (sol) & has
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 503 Date 0/15, 1979
	10.17