WATER WELL REPORT STATE OF OREGON

KLAM 2387 KLAM 2387 FEB 1 4 1985 PLEASE TYPE OF PRINT IN INK

State Well No. 3/5/12E-5aq	State Well No.	375/12E-500
----------------------------	----------------	-------------

	(
State Permit No.	

DALL!	d, Ongood	
(1) OWNER:	(10) LOCATION OF WELL:	
Name Wallace Plemons	County Klamath Driller's well	number
Address P.O. Box 154	NE 4 NE 4 Section 5 T. 37S	R. 12E W.M.
City Beatty State Oregon	Tax Lot # Lot Blk	Subdivision
(2) TYPE OF WORK (check):	Address at well location:	
New Well Deepening □ Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	e ll.
	Depth at which water was first found 54	ft.
	Static level 22" ft. below la	nd surface. Date 1-7-84
Rotary Air M Driven Domestic Industrial Municipal Rotary Mud Dug Irrigation M Test Well Dother	Artesian pressure lbs. per	r square inch. Date
	(12) WELL LOG: Diameter of well below of	easing 8"
CASING INSTALLED: Steel N Plastic	Depth drilled 340 ft. Depth of c	completed well 340 ft.
CASING INSTALLED: Steel	Formation: Describe color, texture, grain size and stru- thickness and nature of each stratum and aquifer penet for each change of formation. Report each change in p and indicate principal water-bearing strata.	rated, with at least one entry
LINER INSTALLED:	MATERIAL	From To SWL
"Diam. from	Brown Clay Soil	0 2
	Broken Blue & Brown Rock	2 12
(6) PERFORATIONS: Perforated? □ Yes 🕱 No	Hard Yellow Clay	12 16
Type of perforator used Size of perforations in. by in.	Blue Sandstone	16 18
	Hard Yellow Clay	18 22
perforations from	Blue Sandstone	22 30
perforations from ft. to ft.	Blue Rock	30 46
perforations fromft. toft.	White Pumie Rock	46 54
(7) SCREENS: Well screen installed? ☐ Yes ☒ No	Hard Blue Rock	54 59
Manufacturer's Name	White Pumie Rock	59 65
Type Model No	Hard Blue Rock	65 106
Diam. Slot Size ft. to ft.	Brown Lava	106 130
Diam. Slot Size Set from ft. to ft.	Grey Basalt	130 175
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Red Rock	175 195 195 294
W'~q a pump test made? ☐ Yes ☑ No If yes, by whom?	Brown Rock	294 328
d: gal/min. with ft. drawdown after hrs.	Red Rock	328 340 22"
" " " "	Hard Grey Basalt)20)40 22
Air test 1000 gal./min. with drill stem at 61 ft. 2 hrs.		
Bailer test gal./min. with ft. drawdown after hrs.		
*-tesian flow g.p.m.		
perature of water 49 Depth artesian flow encountered ft.	Work started 12-8 19 84 Complete	d 1-7 1985
(9) CONSTRUCTION: Special standards: Yes □ No 🔀	Date well drilling machine moved off of well	1-7 1985
Well seal—Material used Cement	(unbonded) Water Well Constructor Certific	cation (if applicable):
Well sealed from land surface to	This well was constructed under my direct s	
Diameter of well bore to bottom of seal	and information reported above are true to my b	est knowledge and belief.
Diameter of well bore below seal8in.	[Signed]	Date, 19
Number of sacks of cement used in well seal 30 sacks	Bonded Water Well Constructor Certification	on:
How was cement grout placed? Pumped.	Bond 28040810 Issued by: Weste	rn Surety Co.
	(number) Sun This well was drilled under my jurisdiction	ety Company Name
37	the best of my knowledge and belief.	-
Was pump installed? N.O	Name Roger Chancellor Well	-Drilling (Type or print)
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.	Address 5223 Valley View Lan	
Did any strata contain unusable water? Yes X No There of Water? don'the of strate	Mary War of 1	
Type of Water? depth of strata	[Signed] William Water Well Construct	or
Method of sealing strata off Was well gravel packed? □ Yes 12 No Size of gravel:		, ₁₉ 85
Gravel placed from		, ==
	· · · · · · · · · · · · · · · · · · ·	