NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

KLAM 3692

WATER WELL REPORT KLAM

STATE OF OREGON
(Please type or print)
(Do not write above this line) ~~14310~~ 3692

State Well No. 39s/8E-28cc

State Permit No. .....

(1) OWNER:

Name Andy Jones

Address RT 3, Box 377 Klamath Falls, Ore.

(2) TYPE OF WORK (check):

New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☑ Driven ☐
Cable ☑ Jetted ☐
☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☑

5/8 Diam. from +1 ft. to 82 ft. Gage .250

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? ☑ Yes ☐ No.

Type of perforator used Factory Perf.

Size of perforations 1/8 in. by X 3 in.

120 perforations from 62 ft. to 82 ft.

perforations from ft. to ft.

perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☑ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☑ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " "

" " "

Bailer test 30 gal./min. with 10 ft. drawdown after 2 hrs.

Artesian flow g.p.m.

Temperature of water 57° Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement

Well sealed from land surface to 31 ft.

Diameter of well bore to bottom of seal 10 in.

Diameter of well bore below seal 8 in.

Number of sacks of cement used in well seal 23 1/2 sacks

How was cement grout placed? pumped Thru 1 1/4" Induction Tube

Was a drive shoe used? ☐ Yes ☑ No Plugs Size: location ft.

Did any strata contain unusable water? ☑ Yes ☐ No

Type of water? Shallow depth of strata 19'

Method of sealing strata off cased and cemented

Was well gravel packed? ☑ Yes ☐ No Size of gravel: 1/2"-

Gravel placed from 62 ft. to 82 ft.

(10) LOCATION OF WELL:

County Klamath Driller's well number

SW ¼ SW ¼ Section 28 T. 39s R. 8E W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 63 ft.

Static level 43' 6" ft. below land surface. Date 5/28/80

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"

Depth drilled 91 ft. Depth of completed well 91 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top soil	0	2	
decomposed lava	2	5	
lava Boulders	5	18	16'
Hard Black lava	18	36	
Brownish Black lava	36	49	
porous Black lava	49	63	
fractured water	63	75	43'6"
Bearing lava			
porous lava	75	91	

RECEIVED
MAY 30 1980
WATER RESOURCES DEPT
SALEM, OREGON

Work started 5/15 1980 Completed 5/28 1980

Date well drilling machine moved off of well 5/27 1980

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Albert M Powell (Drilling Machine Operator) Date 5/28, 1980

Drilling Machine Operator's License No. 114

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Powell Well Drilling (Person, firm or corporation) (Type or print)

Address P.O. Box 114 Keno, Ore.

[Signed] Albert M Powell (Water Well Contractor)

Contractor's License No. 454 Date 5/28, 1980

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*4565G-119