NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 Within 30 days from the date of well completion. SALEM OREGON SALEM OREGON

SALEM, OREGON

State Well No. 24/9-30

State Permit No.

(1) OWNER:	(11) LOCATION OF WELL:
Name CRESCENT WATER ASSOC,	County KLAMOTH Driller's well number
Address PO. BOX 123 (RESCENT ORE	14 14 Section 30 T. 245 R. 9 EW.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well below casing 10 in.
Cable 🔀 Jetted 🗌 📗 Domestic 🗎 Industrial 🗎 Municipal 🕱	Depth drilled 334 ft. Depth of completed well 334 ft.
Dug Bored I Irrigation Test Well Other	Formation: Describe color, texture, grain size and structure of materials;
CASING INSTALLED: Threaded □ Welded 💢	and show thickness and nature of each stratum and aquifer penetrated,
10." Diam. from 0 ft. to 110 ft. Gage 250	with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.
" Diam. from ft. to ft. Gage	MATERIAL From To SWL
" Diam. from ft. to ft. Gage	
PERFORATIONS: Perforated? Yes No.	They Basalt Boulless 6 11
	Black linders 11 16
Type of perforator used	Ped Cinders + Broken Cook 16 43
Size of perforations in. by in.	Gren Baselt Pock 43 120
perforations from ft. to ft.	Broken grees Rock 120/40
perforations from, ft. to ft.	They Esset Rock 140 280
perforations from ft. to ft.	Brown Rock 280 312
perforations from ft. to ft.	Brown Rock with Creywar 312 326
perforations from ft. to ft.	Black Cinder Rock 326 334
(7) SCREENS: Well screen installed? Yes Vo	
(7) SCREENS: Well screen installed? ☐ Yes No Manufacturer's Name	
Type	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WATER LEVEL: Completed well.	
Static level 3/2 ft. below land surface Date 5/15/67	
ian pressure lbs. per square inch Date	
(9) WELL TESTS: Drawdown is amount water level is	
lowered below static level	
Was a pump test made? XYes No If yes, by whom? Klamath Tella	
yield: 350 gal./min. with no ft. drawdown after 24 hrs.	Work started 1966 Completed 6/10 1967
" " "	Date well drilling machine moved off of well 6/14 1969
" " "	Drilling Machine Operator's Certification:
Bailer test 20 gal./min. with 70 ft. drawdown after 4 hrs.	This well was constructed under my direct supervision. Mate-
Artesian flow g.p.m. Date	rials used and information reported above are true to my best knowledge and belief.
Temperature of water	[Signed] KENNETH MATHERSDate VII 1962
	[Signed] KENNETH MATHERSDate 1/11, 1967
(10) CONSTRUCTION:	Drilling Machine Operator's License No. 245
Well seal—Material used BENTIONITE & CEMENT	
Depth of seal #5	Water Well Contractor's Certification:
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Were any loose strata cemented off? Yes No Depth /206/40	NAME MATHERS 4SON
Was a drive shoe used? Yes No	(Person, firm or corporation) (Type or print)
Did any strata contain unusable water? Yes No	Address Pta BOX SER BEND OREGON
Type of water? depth of strata	1/
Method of sealing strata off	[Signed] Lenneth Mathers
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 262 Date 7111 1962