NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

_ filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORTE CEIVED

STATE OF OREGON

(Please type or print)

(Do not write above this WATER RESOURCE Ste DE Hills No. ..

		-			1140	14L	$-<$ \wedge
11/	071	∩ "State	Well	No.	70	/ /	~~~
41	261	9/0		-	295		

of wen completion.	SALEM. CREGON					
(1) OWNER:	(10) LOCATION OF WELL:					
Name Crescent Water Association	county Klamath Driller's well number 758 (22-CP)					
Address P. O. Box 123				W.M.		
Crescent Oregon 97845			E	44.141.		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	on corne	<u>r</u>			
New Well A Deepening Reconditioning Abandon □						
If abandonment, describe material and procedure in Item 12.						
	(11) WATER LEVEL: Completed w	ell.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 335	<u> </u>		ft.		
Rotary Driven Domestic Industrial Municipal Cable Domestic Industrial Municipal	Static level 335 ft. below land s	urface.	Date)	/27/76		
Dug	Artesian pressure lbs. per squar	e inch.	Date			
CACINIC INCMALLED						
CASING INSTALLED: Threaded □ Welded ☑	(12) WELL LOG: Diameter of well b	elow cas	singl	2		
12 "Diam from + 1 ft. to 113 ft. Gage .250	Depth drilled 365 ft. Depth of completed well 365 ft.					
10 " Diam. from 0 ft. to 202 ft. Gage •250	Formation: Describe color, texture, grain size a	nd struc		naterials;		
"Diam. from ft. to ft. Gage ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,					
PERFORATIONS: Perforated? Yes M No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.					
Type of perforator used	374 MWDY47	73	То	swL		
V 2	MATERIAL	From		SWT		
Size of perforations in. by in.	Pumice	0	7			
perforations from ft. to ft.	Hard Boulders	7	18			
perforations from ft. to ft.	Red cinders-large brkn.lava r	· · · · · ·	_50_			
perforations from ft. to ft.	Hard basalt-badly fractured	50_	69_			
(7) SCREENS: Well screen installed? [] Yes [] No	Basalt boulders-Loose grey	(0		· · · · · · · · · · · · · · · · · · ·		
(1) SCREENS: Well screen installed? ☐ Yes ☐ No Manufacturer's Name	cinders	69	77			
	Hard basalt-badly fractured	77	_98_			
Type Model No Diam Slot size Set from ft. to ft.	Basalt boulders-Grey lava ash		777.	· · · · · · · · · · · · · · · · · · ·		
Diam. Slot size Set from ft. to ft.	Hard basalt	777	72),			
Did size Set from	Red cinders	12/1	7/13			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Hard basalt - badly fractured	,	150			
Was a pump test made? ★Yes □ No If yes, by whom? Interstate	Broken grey lava rock Hard black basalt	150 196	196			
	Brown lava rock	295	295			
Kield: 120 gal./min. with 0 ft. drawdown after 21 hrs.	Hard black basalt	377	317	·		
" " "	Grey lava rack	335	335 363			
п п п	Loose grey cinders	363	365 365			
Bailer test 28 gal./min. with 0 ft. drawdown after 1 hrs.	Troope grey criticis	-505-	-305			
Artesian flow g.p.m.						
mperature of water 540 Depth artesian flow encountered ft.	Work started 3/75 19 7), Complete	ad 1, 70	r)	1976		
			(
(9) CONSTRUCTION:	Date well drilling machine moved off of well	4/2	(0/	19 76		
Well seal—Material used Portland Cement	Drilling Machine Operator's Certification:					
Well sealed from land surface toft.	This well was constructed under my	direct	super	vision.		
Diameter of well bore to bottom of sealin.	Materials used and information resorted best knowledge and belief	above §	are true	e to my		
Diameter of well bore below seal 15 in. to 113'-12" to	65 igned It (Drilling Machine Operator)	Date	5/25	19. 76		
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	יייי בייי		.,		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.	717.		***********		
Brand name of bentonite National	TYPE AND THE COURT OF THE COURT			 		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:					
of water133 lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.					
Was a drive shoe used? To Yes 🗌 No Plugs Size: location ft.	Name Carter's Drilling & Pump Service					
Did any strata contain unusable water? ☐ Yes ☐ No	(Person, firm or corporation)	(T	ybe or pr	int)		
Type of water? depth of strata	Address P. O. Box 46 - Springfi	61d/	regor	971.77		
Method of sealing strata off	Tan 1	1.		1		
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	[Signed] (Water Well Contr	actor)	re	<i></i>		
	706		/ 25	10 76		
Gravel placed from ft. to ft.	Contractor's License No Date	24	٠. ــ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ	, 19 <i>L</i> .O		