	L REPORT XLAM State Well No. 27/8-	7.0
ORIGINAL File Original and Duplicate with the STATE ENGINEER, STATE OF		
Duplicate with the STATE OF ST	State Permit No.	
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level	
Name Shell Oil Company	Was a pump test made? ☐ Yes No If yes, by whom?	
Address 1220 S. W. Morrison Street	Yield: gal./min. with ft. drawdown after	hrs.
Portland, Oregon	3) 11 11	"
(2) LOCATION OF WELL:	" " " " " " " " " " " " " " " " " " "	<u></u>
County Klamath Owner's number, if any—	Bailer test 20 gal./min. with 0 ft. drawdown after  Artestan flow g.p.m. Date	Z hrs.
1/4 1/4 Section T. R. W.M.	Artesian flow g.p.m. Date  Temperature of water Was a chemical analysis made?	Yes 🛣 No
HSPURK KKKNY SYNNA KYKNY KARANA KARAN		
Lots 5 and 6, Block 5, Klamath County,	(12) WELL LOG: Diameter of well 12	•
Chemult, Oregon	Depth drilled 234 ft. Depth of completed well 234 ft.	
· · · · · · · · · · · · · · · · · · ·	Formation: Describe by color, character, size of material and str show thickness of aquifers and the kind and nature of the mate stratum penetrated, with at least one entry for each change of	rial in each f formation.
The second secon	777.075	
	MATERIAL	<del></del>
TYPE OF WORK (check):	pumice broken rock with hard & soft lyrs 47	90
New Well Deepening ☐ Reconditioning ☐ Abandon ☐ If abandonment, describe material and procedure in Item 11.	cinders 90	92
	EXTENSE broken rock w/air caves 92	110
(4) PROPOSED USE (check): (5) TYPE OF WELL:	KAKAXKTAKXKAK hard lava 110	
Demestic ☐ Industrial ☐ Municipal ☐ Rotary ☐ Driven ☐ Cable XX Jetted ☐	hard grey rock creviced 163	
gation  Test Well Other 🛣 Dug 🗆 Bored 🗆	red lava rock 215	<b>217</b>
(6) CASING INSTALLED: Threaded Welded	Hard Lava Tock	
(6) CASING INSTALLED: Threaded Welded 7 William from 0 ft. to 119 ft. Gage 250	red lava rock 220	
"Diam, fromft. toft. Gage		
" Diam. fromft_ toft_ Gage		
THE PARTY OF THE P		
(7) PERFORATIONS: Perforated? ☐ Yes XN0  Type of perforator used		
SIZE of perforations in. by in.		·
perforations fromft_ toft		
perforations from ft. to ft.		
perforations fromft. toft.		
perforations fromft_ toft		
perforations from ft. to ft,		
(8) SCREENS: Well screen installed   Yes X No		
ufacturer's Name		
Type Model No.	The state of the s	
Slot size Set from ft. to ft. to ft. to ft.	Work started 4-24-58 19 . Completed 7-8-58	19
D: m Slot size		
CONSTRUCTION:	(13) PUMP:	
well gravel packed?   Yes No Size of gravel:	Manufacturer's Name Advance Pump Company  Type: Jet H.P. 5	
Gravel placed fromft. toft. Was a surface seal provided? ☐ Yes ☐ No To what depth?ft.	Type: Jet H.P. 5	
Matarial used in seal—	Well Driller's Statement:	
Did any strata contain unusable water? Yes No	This well was drilled under my jurisdiction and this report is	
Type of water? Depth of strata	true to the best of my knowledge and belief.	
Method of sealing strata off	NAME A. M. Jannsen Drilling Company	
(10) WATER LEVELS:	(Person, firm, or corporation) (Type or print)  Address 21075 S. W. Tualatin Hiway - Aloha, Orego:	
Static level 213 ft. below land surface Date 7-8-58	Address	
Artesian pressure lbs. per square inch Date	Driller's well number	
Log Accepted by:	[Signed] Swand Il lewiller	
- 10	(Weil Driver)	
[Signed] Date, 19	License No. 79 Date 7-18-58	19