Klam
50223

WATER WELL REPORT
STATE OF OREGON

RECEIVED
MAR 05 1981
WATER RESOURCES DEPT
SALEM, OREGON

State Well No. .....

State Permit No. .....

Application No. G-16179
Permit No.

(1) OWNER:
Name Stan Flesher (Now ~~Jim~~ Cheyles Shuck ranch)
Address Dodds Hollow Rd.
City Merrill, Oregon 97633 State

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary Air ☒ Driven ☐
Rotary Mud ☐ Dug ☐
Cable ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐
Thermal: Withdrawal ☐ Reinjection ☐

(5) CASING INSTALLED:
Steel ☒ Plastic ☐
Threaded ☐ Welded ☐
14" Diam. from 0 ft. to -- ft. Gauge 250
" Diam. from ft. to ft. Gauge

LINER INSTALLED:
" Diam. from ft. to ft. Gauge

(6) PERFORATIONS:
Perforated? ☐ Yes ☒ No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☒ Yes ☐ No If yes, by whom? Art Reed
Yield: 1200 gal./min. with 0 ft. drawdown after 4 hrs.
" "
Air test gal./min. with drill stem at ft. hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 72 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Special standards: Yes ☐ No ☒
Well seal—Material used cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 18 in.
Diameter of well bore below seal 14 in.
Number of sacks of cement used in well seal 20 sacks
How was cement grout placed? grouted in. or pumped in.
Was pump installed? no Type HP Depth ft.
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Klamath Driller's well number
SW ¼ NW ¼ Section 33 T. 40S R. 11E W.M.
Tax Lot # Lot Blk Subdivision
Address at well location: Approx 800 feet east and ~~1~~ 1012 south of the N.W. corner of S33 T40S R 11E

(11) WATER LEVEL: Completed well.
Depth at which water was first found 110 ft.
Static level 110 ft. below land surface. Date 5/20/74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 14
Depth drilled 190 ft. Depth of completed well 190 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top soil brown	0	3	
Lava rock blue grey	3	30	
Lava rock black	30	90	
Red brown lava	90	110	~~110~~
Red lava rock	110	112	110
Blue grey lava rock	112	150	
Broken laa black 7 blue	150	190	110

Work started 4/2 1974 Completed 5/20 1974
Date well drilling machine moved off of well 5/20 1974

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Walter L. Wilson (Drilling Machine Operator) Date 5/20, 1974
Drilling Machine Operator's License No. 201

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Wilson Drilling Cont. Inc. (Person, firm or corporation) (Type or print)
Address P.O. Box 136, Merrill, Oregon 97632
[Signed] Walter L. Wilson (Water Well Contractor)
Contractor's License No. 169 Date 5/20, 1974

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310

SP*12658-690