NOTICE TO WATER WELL CONTRACTOR

The original and first copy of the report 17.7

are to be filed with the WATER WELL REPORT

WATER RESOURCES DEPARTMENT.

SALEM, OREGON 9785 P 2.4 1981

within 30 days from the date

(Please type or print)

of well completion RESOURCES DEP! (Do not write above this line)

State Well No.	2/)5	BE-	$\frac{\partial }{\partial }$	r
----------------	------	-----	-------------------------------	---

State	Well No.	Ç	<u> </u>	195	<u>–</u> a	19	ľ
State	Permit N	To.	**********				

1) OWNER: SALEM. OREGON	(10) LOCATION OF WELL:				
NameKEN WILS'ON	CountKLAMATH Driller's well number				
AddressPA BAX 173	NW 4NE 4 Section 21 T.275R. 8 E W.M.				
CHEMULT OKE.	Bearing and distance from section or subdivision corner				
2) TYPE OF WORK (check):					
Yew Well					
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.				
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 220 ft.				
Rotary Driven Domestic Mindustrial Municipal Domestic	Static level 220 ft. below land surface. Date//-/4-82				
Oug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date				
CASING INSTALLED: Threaded Welded Welded M. Gage 150. 5 "Diam. from ft. to 60 ft. Gage 150. 5 "Diam. from tt. to 65 ft. Gage 150.	(12) WELL LOG: Diameter of well below casing 6. Depth drilled 250 ft. Depth of completed well 250 ft.				
" Diam. from ft. to ft. Gase 3.80	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.				
PERFORATIONS: Perforated? Yes No.	MATERIAL From To SWL				
Size of perforations in. by in.	PUMICE 08				
perforations fromft. toft.					
perforations from ft. to ft.	CLAY BOLDERS 8 50				
7) SCREENS: Well screen installed? Wes No	BROKEN ROCK 50 100				
Manufacturer's Name	LAVA ROCK VOD 150 120				
Type Model No.					
Diam. Slot size Set from ft. to ft.					
Diam Slot size Set from ft. to ft.					
(8) WELL TESTS: Drawdown is amount water level is lowered below static level					
Was a pump test made? Yes □ No If yes, by whom? H, MAY					
Yield: 3,5 gal./min. with t. drawdown after hrs.					
" " " " "					
п п н	- Spa				
Bailer test gal./min. with ft. drawdown after hrs.					
Artesian flow g.p.m.					
perature of water 2 Depth artesian flow encountered	Work started 4 - 4 - 28 19 80 Completed / - / 8 19 80				
	Work started 19 60 Completed 19 80 Completed 19 80 Date well drilling machine moved off of well 19 80				
(9) CONSTRUCTION:					
Well seal—Material used CEMENT	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.				
Well sealed from land surface to 3.	Materials used and information reported above are true to my				
Diameter of well bore to bottom of seal in.	best knowledge and belief.				
Number of sacks of cement used in well sealsacks	[Signed] Date Date 1980				
How was cement grout placed? PUMP	Drilling Machine Operator's License No				
	Water Well Contractor's Certification:				
	This well was drilled under my jurisdiction and this report is				
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.				
Old any strata contain unusable water? 🗍 Yes 🔏 No	(Person firm or corporation) (Type or print)				
Type of water? depth of strata	Address TAR, RTE GILCHRIST, ORE,				
Method of sealing strata off	150 may				
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contractor)				
Gravel placed from ft. to ft.	Contractor's License No. 536 Date//- 20 1980				
	<u> </u>				