Instructions for completing this report are on the last page of this form

(START CARD) # 133631

| (1) OWNER: Well Number | (9) LOCATION OF WELL by legal description: County KLAMATH Latitude Longitude Township 39S N or S. Range 08E E or W. of WM. | | | | | | |
|---|---|---|------------------------|-----------------|---------------------------|-----------------|----------|
| Address 13350 HWY, 66 City KLAMATH FALLS State OR | Section 32 NW 1/4 SW 1/4 | | | | | | |
| (2) TYPE OF WORK: | | Tax lot 200 Lot Street Address of Well (KLAMATH FALL | or nearest address) 1 | | Subdivis VY. 66 | | |
| New Well Deepening Alteration (repair/recondi | tion) Abandonment | | | | | | |
| (3) DRILL METHOD: Rotary Air | (10) STATIC WATER LEVEL: 16 ft. below land surface. Date 7/3/2001 Artesian pressure lb. per square inch. Date | | | | | | |
| | | (11) WATER BEARIN | | | | | |
| (4) PROPOSED USE: | X Irrigation | Depth at which water wa | s first found 7 FT. | | | | |
| Domestic Community Industrial Thermal Injection Livestock | From | То | Estimat | nated Flow Rate | | SWL | |
| (5) BORE HOLE CONSTRUCTION: | 7 | 8 | + | GPM . | | 7 | |
| • • | ompleted Well 378 ft. | 183 331 | 331 374 | 1300 | GPM GPM | | 16 16 |
| provide provide a second | mount | | | 1000 | O1 W | | |
| HOLE SEAL Diameter From To Material From T | (12) WELL LOG: Ground elevation 4150 | | | | | | |
| 16 0 18.5 BENTONITE 0 18 10 18.5 366 | | | | | | | |
| 8 366 378 | | TOP SOIL | aterial | | rom O | To 4 | SWL |
| | | SANDY BROWN CL | | | 4 | 9 | 7 |
| | | BLACK & BROWN L | AVA ROCK & B | ROWN | 9 | 42 | |
| How was seal placed: Method A B C D | []E | BLACK ROCK | | | 13 | 13 23 | |
| X Other POURED | | BLACK & BROWN L | AVA ROCK & B | ROWN | 23 | | |
| Backfill placed from ft. to ft. Material Gravel placed from ft. to ft. Size of grav | el | CLAY BLACK LAVA ROCH | (& BI HE CLAY | | 58 | 58 108 | |
| | | BLACK & BROWN L | | ROWN | 108 | 100 | |
| (6) CASING/LINER: Diameter From To Gauge Steel Plas | tic Welded Threaded | CLAY | AV/A DOOK DE | | | 183 | |
| Casing: 10 +1.5 18.5 .250 X | X | BLACK & BROWN L | | ט | 183 | 220 | 16 |
| | | BLACK & BROWN L | | ROWN | 220 | | |
| | | CLAY | V O DDOMALLAN | VA BOC | 1004 | 331 | 16 |
| Liner: NONE | | FRACTURED BLAC | K & BROWN LA | VA RUC | 1031 | 374 | 16 |
| | | BLACK ROCK | | | 374 | 378 | |
| Final location of shoe(s) NONE | | RECI | EIVED | | | | |
| (7) PERFORATIONS/SCREENS: | | | | | | | |
| Perforations Method NONE Screens Type Materi | al | JUL 0 | 9 2001 | | | | 711 2400 |
| Screens Type Materi | | WATER RESO | LIBCES S- | | | | |
| From To size Number Diameter size NONE | Casing Liner | SALEM, (| DREGON | | | | |
| | | Date started 6/27/2001 | Comp | oleted 7/3 | /2001 | | |
| | | (unbonded) Water Well | | | | | |
| | | I certify that the work I per | formed on the construc | ction, altera | ation, or | abandor | nment |
| (8) WELL TESTS: Minimum testing time is 1 h | our | of this well is in compliance Materials used and informat | | | | | |
| Pump Bailer XAir | Flowing Artesian | belief. | _ | | | er 156 (| |
| Yield gal/min Drawdown Drill stem at Time | | Signed J. Brut | Pinhand | | 7/6/20 | | |
| 600 GPM 150 FT. | 1 hr. | | - | | | | |
| | Marrier - Francisco M Francisco M. A FF Francisco M. A FF Francisco Marrier - | (bonded) Water Well Co | | | han-1 | | . |
| | | I accept responsibility for t performed on this well durin | | | | | |
| Temperature of Water 64 F Depth Artesian Flow fou | performed during this time is | s in compliance with O | regon wate | er suppl | y well | | |
| Was a water analysis done? Yes By whom Did any strata contain water not suitable for intended use? | construction standards. This report is true to the best of my knowledge and belief. WWC Number 777 | | | | | | |
| Salty Muddy Odor Colored X Other St | Signed Steplier | R Guelies | | 7/6/20 | | | |
| Depth of strata: 7' TO 8' | | | | | | | |